

XXVI Convegno Nazionale



ASSOCIAZIONE ITALIANA di SCIENZA
e TECNOLOGIA delle
MACROMOLECOLE



Torino, 6-9 Settembre 2026

Organized by



UNIVERSITÀ
DI TORINO



Politecnico
di Torino




UNIVERSITÀ DEL PIEMONTE ORIENTALE

Supported by



Anton Paar

METTLER TOLEDO



Book of Abstracts



Indice dei **CONTENUTI**

- 03** il programma
 - 10** la lista dei posters
 - 13** il comitato scientifico
 - 15** il comitato promotore AIM
 - 17** il comitato organizzatore
 - 18** la segreteria organizzativa
 - 19** i plenary speakers
 - 20** le plenary lectures
 - 24** i keynotes
 - 32** altri contenuti orali
 - 33**
 - polimeri da fonti rinnovabili e degradabili, riciclo
 - 61**
 - materiali polimerici ibridi e (nano)compositi – sintesi caratterizzazione e applicazioni
 - 91**
 - processabilità e stampa 3D di materiali polimerici
 - 98**
 - chimica e fisica dei polimeri
 - 107** i posters
 - 108**
 - polimeri da fonti rinnovabili e degradabili, riciclo
 - 121**
 - materiali polimerici ibridi e (nano)compositi – sintesi caratterizzazione e applicazioni
 - 133**
 - processabilità e stampa 3D di materiali polimerici
 - 135**
 - chimica e fisica dei polimeri
-

PROGRAMMA

-  Plenary lecture
-  Keynote lecture

-  Polimeri da fonti rinnovabili e degradabili, riciclo
-  Materiali polimerici ibridi e (nano)compositi: sintesi, caratterizzazione e applicazioni
-  Processabilità e stampa 3D di materiali polimerici
-  Chimica e fisica dei polimeri



DOMENICA 6 SETTEMBRE

	Politecnico di Torino – Corso Duca degli Abruzzi 24	
18:00		Registrazione
19:00		Welcome party

LUNEDÌ 7 SETTEMBRE

	Polo Biotecnologico dell'Università di Torino (Via Nizza 52)	
8:30		Registrazione
9:00		Apertura lavori - Sala Keplero
		Chairperson: R. Bongiovanni
9:10	PL1	Y. Leterrier (Ecole Polytechnique Fédérale de Lausanne) Robust superhydrophobic composite surfaces
10:00	KN1	A. Dodero (University of Fribourg) Block copolymer self-assembly in emulsions: from structural-color microparticles to multifunctional and reprogrammable photonics
10:30		Coffee break

PARALLEL SESSIONS

			
Sala Keplero		Sala Leonardo	
			
Chairperson: M. Salzano de Luna		Chairperson: R. Simonutti	
11:00	O1.1	O3.1	
	A. Barbato (Università di Salerno) Development of active biodegradable PLA/PBSA films containing blueberry waste antioxidants extracted using nades as green solvents	A. Bardelli (Università di Genova) From marine plastic litter to 3D printing: optimising blended polyolefin formulations for additive manufacturing	
11:15	O1.2	O3.2	
	B. Brugnoli (Università di Roma – La Sapienza) Multifunctional eugenol-based nanogels through copolymer design: antioxidant activity, intrinsic fluorescence, and drug encapsulation	R. Di Girolamo (Università di Napoli Federico II) In situ stereocomplex formation during melt extrusion: an efficient nucleating strategy for crystallization of high-molecular weight PLA	
11:30	O1.3	O3.3	
	A. D'lorio (Università di Ferrara) Solvent-free grafting of pbs oligomers onto cellulose nanofibers for enhanced biocomposite compatibility	A. Sorze (Università di Trento) Effect of natural fillers as substitutes for glass fibers in polyamide 6 composites for large-format additive manufacturing	
11:45	O1.4	O3.4	
	M.R. Acocella (Università di Salerno) Mechanochemical polymer-to-polymer recycling of polylactic acid	E. Togliatti (Università di Parma) Influence of graphene on the electrical and mechanical properties of SLS-printed PA11	
12:00	O1.5	O3.5	
	F. Bisio (Università del Piemonte Orientale) (Meth)-acrylated tannic acid as a bio-based adhesion promoter for EB-curable coatings	D. Rigotti (Università di Trento) Fused filament fabrication of TPU/PCM composites for thermally active wearable sport applications	
12:15	O1.6	O3.6	
	G. Damonte (Università di Genova) Environmentally friendly upcycling of PHA-based copolymers into branched multifunctional oligomers	A. Caccini (Politecnico di Milano) Extending rubber fracture characterisation methods to layer adhesion assessment in 3D-printed TPU	
12:30		Lunch time	

LUNEDÌ 7 SETTEMBRE (cont.)

		Sala Keplero	
		<i>Chairperson: K. Sparnacci</i>	
14:30	KN2	V. Ambrogì (Università di Napoli Federico II) Rethinking epoxy thermosets: from dynamic networks to circular materials	
SESSIONI PARALLELE			
		 Sala Leonardo	
		 <i>Chairperson: C. Marano</i>	
15:00	O1.7	M. Calosi (Università di Ferrara) Amorphous blends of PLA and PHA for waterborne coatings and foam applications	O2.1 A. Bifulco (Università di Napoli Federico II) Transparent and self-extinguishing silica-epoxy nanocomposites based on Novolac resin
15:15	O1.8	R. Chiarcos (Università del Piemonte Orientale) Investigation into the potential of poly(β -amino ester)-based vitrimers	O2.2 L. Broggio (Università di Trento) Solvent-free processing of high β -phase poly(vinylidene fluoride) films for energy conversion applications
15:30	O1.9	S. Alfano (Università di Roma – La Sapienza) Formulation and characterization of polyhydroxyalkanoate blends with waste protein fibers for packaging application	O2.3 E. Buratti (Università di Ferrara) Hybrid microgels based on PNIPAM and natural proteins: from molecular interactions to biomaterial applications
15:45	O1.10	A. Giovagnoli (Università di Bologna) Development and industrial processing of cellulose-based materials for rigid packaging applications	O2.4 M.T. Letizia (Istituto Universitario di Studi Superiori Pavia) Towards sustainable electrical cable insulation: design of a novel polyethylene-based composite system
16:00	O1.11	D. Gaikwad (Università Milano Bicocca) Use of fruit peels for the development of bio-based hydrogels	O2.5 C. Ciarlantini (Università di Roma – La Sapienza) Cyclodextrin-grafted chitosan scaffolds for enhanced curcumin delivery
16:15	O1.12	G. Filippone (Università di Napoli Federico II) Effect of processing pressure on the interfacial shear strength in short fiber biocomposites: implications for manufacturing	O2.6 B. Bertoncini (Università di Pisa) Long vs. short chain covalent functionalization in the preparation of mechanochromic polymers
16:30		<i>Coffee break</i>	
18:00		<i>Torino Tour – Ritrovo in Piazza San Carlo, di fronte al monumento</i>	

MARTEDÌ 8 SETTEMBRE

	Polo Biotecnologico dell'Università di Torino (Via Nizza 52)	
	Sala Keplero	
	Chairperson: G. Malucelli	
9:00	PL2	D. Beneventi (University Grenoble Alpes) Cellulose fibres and derivatives: from traditional papermaking to advanced additive manufacturing
9:50	KN3	S. Losio (Istituto di Scienze e Tecnologie Chimiche) Cyclic olefin based copolymers via transition metal catalysis: bridging synthesis and functional application
10:20		Coffee break
SESSIONI PARALLELE		
	Sala Keplero	 Sala Leonardo
	Chairperson: A. Dorigato	 Chairperson: A. Pucci
10:50	O2.7	A. Bianucci (Politecnico di Milano) Effect of silane coupling agent content on strain-induced cavitation in silica-filled SBR
11:05	O2.8	S. Gabellini (Università di Bologna) Synthesis and nanostructuration of DPP-based fluorescent polyesters for bioimaging
11:20	O2.9	C. Imparato (Università di Napoli Federico II) Silica-based nanostructured mixed oxides via sol-gel for the enhancement of fire resistance and recyclability of epoxy resins
11:35	O2.10	L. Gianoglio (Università di Torino) Electrospun maltodextrin-derived carbon fibers: a sustainable platform for gold-based catalysts
11:50	O2.11	A. Liguori (Università di Bologna) Multifunctional and sustainable vitrimer systems
12:05	O2.12	A. Nicosia (Università di Catania) Functional polymers for the optical detection of amines: from bio-inspired to natural sensing units
12:20	O2.13	M. Righetti (Università di Torino) Intercalated sodium bentonite in thermoplasticized corn starch: tuning oxygen barrier and mechanical performance for flexible food packaging applications
12:35	O2.14	F. Passoni (Politecnico di Milano) Study of the high-pressure H ₂ exposure effect on the mechanical behaviour of nbr based compounds
	O4.1	C. Cecone (Università di Torino) Electrospun membranes obtained from plant proteins and maltodextrins for the treatment of gadolinium-contaminated wastewater
	O4.2	M. Turriani (Università di Pisa) From amphiphilic random copolymers to functional nano-chelators: a new strategy for radionuclides sequestration
	O4.3	L. Tosato (Università di Bologna) A novel melamine-free waterborne intumescent coating for fire protection of wood
	O4.4	J.A. Talamo Ruiz (Politecnico di Torino) Electrospinning and solution blow spinning of water-based polymer solutions for the sustainable manufacturing of nanofibrous mats
	O4.5	M. Scotti (Università di Napoli Federico II) Tacticity-independent crystallization as a design strategy for chemically recyclable semicrystalline polymers
	O4.6	G. Pignatiello (Università di Napoli Federico II) Structure-property relationships in biopolymeric cryogels produced by freeze-casting
	O4.7	F. Olla (Politecnico di Milano) Pressure-induced crystallization and polymorphic transitions of polybutene-1: high-pressure PVT study
	O4.8	E. Guazzelli (Università di Pisa) HEMIN-based amphiphilic random copolymers as biomimetic and recyclable catalysts for ARGET-ATRP in water
13:00		Lunch time

MARTEDÌ 8 SETTEMBRE (cont.)

		Sala Keplero		
		<i>Chairperson: P. Bracco</i>		
14:30	KN4	C. Zagni (Università di Catania) Functionalized polymeric materials: versatile macromolecular platforms for pharmaceutical and environmental applications		
SESSIONI PARALLELE				
				
Sala Keplero		Sala Leonardo		
				
<i>Chairperson: P. Russo</i>		<i>Chairperson: D. Caretti</i>		
15:00	O1.13	M. Colombo (Politecnico di Milano) Structural control and amyloid reinforcement of waste-derived protein films	O2.15	L. Simonini (Università di Trento) Development and characterization of sandwich composites with thermal management and mechanical properties
15:15	O1.14	V. La Matta (Università di Napoli Federico II) Prospective life cycle assessment of tyre manufacturing: evaluating industrial decarbonisation pathways	O2.16	R. Medri (Università di Bologna) Eco-friendly dye-porphyrin copolymer for organic solar cells: from ternary donor to interfacial layer
15:30	O1.15	N. Ferrentino (Università di Salerno) From thiol-ene chemistry to bio-based polymeric networks: multifunctional limonene-derived materials	O2.17	A. Riccioni (Politecnico di Torino) Furanized cellulose nanocrystals for the preparation of diels-alder rubber composites
15:45	O1.16	C. Di Bernardo (Politecnico di Torino) Emerging concepts for sustainable biocomposites	O2.18	R. Rossi (Università di Firenze) Smart polymeric architectures based on photoswitches: from adhesives to responsive nanocarriers
16:00	O1.17	A. Longo (IPCB-CNR) Tuning PLLA Crystallization Kinetics via Reactive Extrusion Branching Strategies	O2.19	P. Stagnaro (SCITEC-CNR) Engineered polymer-based composites for radiative cooling systems
16:15		<i>Coffee break</i>		
16:30	O1.18	M. Mollo (Politecnico di Torino) Designing vanillin-based dynamic networks for the development of sustainable thermosets for future generation composites	O2.20	L. Vitiello (IPCB-CNR) Enhanced hydrolytic degradation of pla green composites by nanometric zno covalently bound on natural fibres via ALD
16:45	O1.19	E. Pellegrino (Politecnico di Torino) Melt-processing of dialcohol cellulose fibres/starch blends: processing strategies, structure and properties	O2.21	V. Spinoso (Università di Firenze) Capacitive sensor based on porous liquid crystalline gel
17:00	O1.20	V. Giglio (IPCB-CNR) Beyond biodegradability: comparative lc-ms profiling of plastic additive release from fossil-based and biodegradable agricultural mulch films into soil	O2.22	A. Pucci (Università di Pisa) Pyrolysis-derived telechelic polypropylene as a mechanochromic probe for visualizing stress redistribution and cavitation in polyolefin-based materials
17:15	O1.21	C. Invigorito (Anton Paar) Multiscale polymer analysis: correlating chemical structure, thermal behavior, and rheological response through complementary analytical techniques		
17:30		<i>Assemblea dei Soci</i>		
18:00		<i>Sessione Poster</i>		
20:30		<i>Cena di gala @OGR Officine Grandi Riparazioni, Corso Castelfidardo, 22</i>		

MERCOLEDÌ 9 SETTEMBRE

	Polo Biotecnologico dell'Università di Torino (Via Nizza 52)	
	Sala Keplero	
	Chairperson: M. Zanetti	
9:00	PL3	A. Figoli (Istituto per la Tecnologia delle Membrane - CNR) Innovative polymerised tailored membranes for gas and liquid applications
9:50	KN5	D. Martella (Università di Firenze) 3D printing meets liquid crystal polymers: responsive materials across different scales and applications
10:20		Coffee break
SESSIONI PARALLELE		
	Sala Keplero	 Sala Leonardo
	Chairperson: M. Messori	 Chairperson: M. Castellano
10:50	O1.21	D.H. Lamparelli (Università di Salerno) When molecular imperfection works: sustainable polyester copolymers with industrial potential
11:05	O1.22	P. Russo (IPCB-CNR) Natural antioxidant effect of hazelnut shell powder in PBS biocomposites under accelerated UV aging
11:20	O1.23	C. Noè (Politecnico di Torino) Bio-based and antifungal by design: UV-cured eso/essential oil composites for next-generation active packaging
11:35	O1.24	C. Pellicchia (Università di Salerno) Engineering circular polyesters through molecular architecture: from thermoplastic elastomers to dynamic covalent networks
11:50	O1.25	R. Sergi (Università di Roma – La Sapienza) Eugenol-derived polymeric networks as eco-friendly and circular wet-strength agents for high-performance paper products
12:05	O1.26	F. Cano (Università di Torino) Mechanical recycling of multi coupled material body seals based on thermoplastic elastomers in the automotive industry
12:20		O2.29
		A. Fusari (Politecnico di Milano) Investigating bacteria-driven alginate hydrogel matrix degradation: a rheological framework to discriminate between crosslinker depletion and backbone cleavage
13.00		Lunch time



METTLER TOLEDO



MERCOLEDÌ 9 SETTEMBRE (cont)



Sala Keplero



Chairperson: G. Filippone

14:00

KN6

M. Bertoldo (Università di Ferrara)
Polyesters in water: from dispersion strategies to functional applications

14:30

KN7

D. Natali (Ecole Polytechnique Fédérale de Lausanne) *Macrogiovani 2026 Winner*
4D-Printable shape morphing double network granular elastomers (DNGEs)

15:00



Conclusioni e saluti finali

15:30



Coffee break

LISTA DEI POSTERS

POSTER

Polimeri da fonti rinnovabili e degradabili, riciclo	
P1.1	B. Cavallo (Università di Torino) Development of cellulose fibers recovery strategy from siliconized papers
P1.2	M. Ceraulo (Università di Palermo) PBAT/grape pomace biocomposite for film blowing applications
P1.3	S. Coiai (ICCOM-CNR) Antioxidant and UV-blocking poly(butylene succinate) films via nitroxide radical coupling functionalization
P1.4	E. Di Francesco (Università di Genova) Thermal method to recover glass fibers from epoxy resin composites
P1.5	M. Di Maro (STEMS-CNR) Influence of fast pyrolysis bio-oil-derived phenolic-rich fraction on PLLA UV stability
P1.6	G. Fredi (Università di Trento) Polyethylene glycol-assisted film stacking of polylactide/bacterial cellulose nanocomposites for sustainable food packaging
P1.7	L. Gianoglio (Università di Torino) Biopol4Soil- Bioderived polymeric granules and non-woven fabrics for sustainable agriculture: biodegradability and phytotoxicity evaluation
P1.8	C. Meo (Università di Ferrara) Characterization of hydrolyzed polyesters from agro-waste: effect of extraction conditions on composition
P1.9	M.C. Mistretta (Università di Palermo) Influence of glioclids and compatibilizer on the rheological, mechanical and biodegradation behaviour of PBAT and PLA biocomposites
P1.10	P. Scarfato (Università di Salerno) Circular valorization of post-consumer polyurethane foams through mechanical recycling and sustainable composite design
P1.11	R. Simonutti (Università di Milano Bicocca) Itaconic Acid: a sustainable platform alternative to acrylic acid in radical polymerization
P1.12	S. Zeynalova (Politecnico di Torino) Biobased vitrimers using eutectic hardener systems

Materiali polimerici ibridi e (nano)compositi: sintesi, caratterizzazione e applicazioni	
P2.1	E. Caianiello (IPCB-CNR) Graphene oxide functionalization of bacterial cellulose: effects on the structure and adsorption performance
P2.2	F. Cicogna (ICCOM-CNR) Residual antioxidant activity of winery by-product biofillers in LDPE and HDPE composites
P2.3	L. Conzatti (SCITEC-CNR) Upcycling hazelnut by-Products into functional elastomeric composites for sustainable sports surfaces
P2.4	R. D'Auria (IPCB-CNR) Development of lignin-containing biodegradable polymer blends for fishing net applications
P2.5	D. Errico (Università di Ferrara) Preparation and characterization of thermoresponsive films obtained from hybrid PNIPAM/silk fibroin systems
P2.6	T. Landovsaky (Institute of Physics of the Czech Academy of Sciences) Stabilization of magnetic nanoparticles in liquid crystalline polymers via tailor-made ligands
P2.7	V. Fiore (Università di Palermo) Development of PBSA-based biocomposites reinforced with ceiba speciosa natural fibres
P2.8	G. Malucelli (Politecnico di Torino) Physics-informed machine learning for predicting optical transmittance and haze in transparent wood
P2.9	G. Malucelli (Politecnico di Torino) Preparation and characterization of UV-LED curable bio-based coatings containing polymeric carbon dots
P2.10	G. Malucelli (Politecnico di Torino) Sustainable transparent wood based on bio-based isobornyl acrylate/methacrylate matrices
P2.11	M. Morreale (Università di Enna "Kore") Microplastics release from pp-based blends and nanocomposites

Processabilità e stampa 3D di materiali polimerici

P3.1	R. Arrigo (Politecnico di Torino) Processing as a design tool for tailoring microstructure and properties in complex polymer systems
------	--

Chimica e fisica dei polimeri

P4.1	A. Bandini (Università di Pisa) Fluorine-free proton exchange membranes: synthesis and characterization of sulfonated PPO-PBI networks for pemwec
P4.2	A. Frache (Politecnico di Torino) Towards circular flame-retarded polypropylene: fire performance after recycling and aging
P4.3	S. Pragliola (Università di Salerno) Design of carbazole-functionalized poly(triphenylamine)s for VISIBLE-driven water remediation

COMITATO ^{TL}SCIENTIFICO



Sabrina Carola Carroccio

IPCB-CNR Catania



Silvia Vicini

UNIGE



Katia Sparnacci

UPO



Riccardo Chiarcos

UPO



Alberto Fina

POLITO

COMITATO ^{TL}SCIENTIFICO



Massimo Messori

POLITO



Marco Sangermano

POLITO



Valentina Brunella

UNITO



Claudio Cecone

UNITO

COMITATO PROMOTORE AIM



Sabrina Carola Carroccio



Chiara Gualandi



Silvia Vicini



Martina Salzano de Luna



Paolo Lomellini

COMITATO PROMOTORE AIM



Fiorenzo Parinello



Giulio Malucelli

^{IL}COMITATO ORGANIZZATORE



Roberta Bongiovanni

POLITO




Pierangiola Bracco

UNITO



Michele Laus

UPO



Giulio Malucelli

POLITO



Marco Zanetti

UNITO



Diego Antonioli

UPO

^{La} SEGRETERIA ORGANIZZATIVA



Diego Antonioli



Patrizia Barraco



Andrea Batistini



Maria Graziella Viola

Ecco i PLENARY SPEAKERS



Ives Leterrier

EPFL Zurigo
Svizzera



Davide Beneventi

CNRS Grenoble
Francia



Alberto Figoli

ITM-CNR
Italia

PLENARY SPEAKERS

Plenary Lectures

ROBUST SUPERHYDROPHOBIC COMPOSITE SURFACES

Yves Leterrier

Laboratory for Processing of Advanced Composites (LPAC)
Ecole Polytechnique Fédérale de Lausanne (EPFL)
CH-1015 Lausanne, Switzerland
e-mail: yves.leterrier@epfl.ch

The presentation is an overview of the activities carried out at the EPFL to produce robust bioinspired polymer composite surfaces [1]. Focus is on integrative synthetic strategies based on photopolymerization to achieve superior property combination such as self-cleaning, antireflectivity and wear-resistance. Hybrid organic-inorganic nanocomposites are produced using acrylate, epoxy and organosilane precursors with surface-treated silica nanoparticles and microfibrillated cellulose via a dual cure photopolymerization and thermal condensation process [2]. The dynamics of network formation are investigated using photo-hyphenated methods such as photo-rheology and photo-calorimetry. The optimization of the dual cure sequence, with the right timing of the photo-exposure vs. condensation leads to an improved printability and nanoscale shape fidelity owing to a reduced viscosity, and a superior hardness, up to several 100 MPa with a high loading of preformed particles. The addition of a reactive surfactant into the hybrid formulation further enables to control the surface energy of the composite via an enthalpy gradient migration from the bulk to the composite-air interface [3]. The subsequent replication of the surface of lotus leaves and rose petals with hierarchical roughness leads to superhydrophobic surfaces that are wear-resistant [4,5]. Ongoing work investigates photo-reversible chemistries to add self-repair and reshaping performance to the property portfolio.

1. González Lazo M.A., Katrantzis I., Dalle Vacche S., Karasu F., Leterrier Y., A Facile in Situ and UV Printing Process for Bioinspired

Self-Cleaning Surfaces, *Materials*, 9, 738 (2016). DOI 10.3390/ma9090738.

2. Poothanari M.A., Schreier A., Missoum K., Bras J., Leterrier Y., Photo-Cured Nanocellulose Composites: Recent Advances, *ACS Sustainable Chem. Eng.* 10, 3131–3149 (2022). DOI 10.1021/acssuschemeng.1c07631.

3. Wasser L., Dalle Vacche S., Karasu F., Müller L., Castellino M., Vitale A., Bongiovanni R., Leterrier Y., Bio-Inspired Fluorine Free Self-Cleaning Polymer Coatings, *Coatings*, 8, 436 (2018). DOI 10.3390/coatings8120436.

4. Cully P., Karasu F., Müller L., Jauzein T., Leterrier Y., Self-Cleaning and Wear-Resistant Polymer Nanocomposite Surfaces, *Surf. Coat. Technol.*, 348, 111–120 (2018). DOI 10.1016/j.surfcoat.2018.05.040.

5. Balkan A., Sola E., Karasu F., Leterrier Y., Photo-Curable Thiol-Ene / Nanocellulose Elastomeric Composites for Bio-Inspired and Fluorine-Free Superhydrophobic Surfaces, *ACS Appl. Mater. Interfaces*, 16, 61144–61156 (2024). DOI 10.1021/acsami.4c16445.

CELLULOSE FIBRES AND DERIVATIVES: FROM TRADITIONAL PAPERMAKING TO ADVANCED ADDITIVE MANUFACTURING

Davide Beneventi

LGP2, Grenoble Institute of Technology, CNRS, University Grenoble Alpes, Grenoble, France
e-mail: davide.beneventi@pagora.grenoble-inp.fr

Cellulose and its derivatives have long been base raw materials in the paper, board, and textile industries, with more limited but well-established roles as functional additives in battery manufacturing, coatings, and food processing.

Over the past fifteen years, the emergence of cellulose nanofibers (CNFs) and cellulose nanocrystals (CNCs) has substantially broadened the accessible properties space of these materials. Namely, from high-strength natural fibres to film-forming soluble derivatives, with microfibrillated cellulose and nanocelluloses occupying an intermediate space of tunable mechanical and physicochemical characteristics.

A key enabler for additive manufacturing has been the specific rheological behaviour of nanocellulose-based hydrogels: shear-thinning under nozzle flow and rapid structural recovery upon deposition. This has overcome the historically poor processability of native cellulosic fibres, paving the way to cold-extrusion 3D printing of cellulose pastes, hydrogels, and composite inks.

Application domains span a surprisingly broad range. Indeed, beyond the most cited example of tissue engineering scaffolds, the literature reports CNF hydrogels for stimuli-responsive drug delivery, conductive nanocellulose composites for flexible pressure sensors and wearable electronics, electrodes for enzymatic biofuel cells and electrochemical biosensors, as well as structural components with high thermomechanical performance from thermoset biocomposite pastes. The biodegradability, non-toxicity, and renewability of nanocelluloses make them particularly attractive across all these contexts.

This contribution provides an overview of how cellulose, in its various forms, has been formulated into hydrogels and composite pastes for the additive manufacturing of functional devices and structural objects, and of where this rapidly evolving field currently stands.

INNOVATIVE POLYMERISED TAILORED MEMBRANES FOR GAS AND LIQUID APPLICATIONS

A. Figoli

Institute on Membrane Technology “EnricoDrioli” – National Research Council of Italy,
Via P. Bucci 17c, 87050, Rende (CS), Italy

e-mail: alberto.figoli@cnr.it

Membrane technology is applied with success in many industrial fields and in some of them, as desalination and wastewater treatment, it can be considered a dominant technology.

Recently, innovative polymerizable functionalized membranes have been developed and the possibility of tailoring them allowed to use for a wider number applications.

Three case studies on innovative polymerized membranes in water treatment, gas separation and water electrolysis for producing green hydrogen will be reported and discussed in details, showing the potentiality and the versatility of this innovative approach [1-4]. Moreover, several factors, as the operating parameters and the membrane functionalities materials, influencing the performance of the membrane process will be discussed and future prospects will be also highlighted.

References

1. F. Galiano, A step forward to a more efficient wastewater treatment by membrane surface modification via polymerizable bicontinuous microemulsion, *Journal of Membrane Science*, 482 (2015) 103
2. A. Figoli et al. Bicontinuous microemulsion polymerized coating for water treatment, WO/2015/044335A2, 2015.
3. A. Figoli et al. Membranes containing polymerized ionic liquid for use in gas separation WO/2019/171409, 2019.
4. F. Galiano et al. Phosphonium ionic liquid-polyacrylate copolymer membranes for improved CO₂ separations, *Journal of Membrane Science* 635 (2021) 119479
5. E. Fontananova et al. CytoCell@PIL: A New Citrus Nanocellulose-Polymeric Ionic Liquid Composite for Enhanced Anion Exchange Membranes, *Chemical Engineering Journal Advances* 25 (2026) 101007

I KEYNOTES

BLOCK COPOLYMER SELF-ASSEMBLY IN EMULSIONS: FROM STRUCTURAL-COLOR MICROPARTICLES TO MULTIFUNCTIONAL AND REPROGRAMMABLE PHOTONICS

A. Dodero^{1,2}

¹ Adolphe Merkle Institute, University of Fribourg, Chemin des Verdiers 4, 1700, Fribourg, Switzerland

² National Center of Competence in Research (NCCR) Bio-Inspired Materials, Chemin des Verdiers 4, 1700, Fribourg, Switzerland

e-mail: andrea.dodero@unifr.ch

Controlling structural color through scalable, precise, and multifunctional materials design remains a central challenge in the development of next-generation photonic materials. Here, we present a versatile approach based on the confined self-assembly of block copolymers (BCPs) within emulsion droplets, enabling the fabrication of photonic microparticles with highly ordered internal nanostructures and vivid structural colors. By exploiting supramolecular additives and low-molecular-weight swelling agents, the photonic bandgap can be tuned across the visible spectrum through controlled variations in domain periodicity and refractive-index contrast. This strategy enables broad spectral control while preserving the structural integrity of the particles and their compatibility with scalable emulsification processes. Building on this materials platform, the photonic microparticles can be translated into practical water-based structural-color coatings by dispersing them in polymeric binders and combining them with broadband absorbers. The resulting formulations generate vivid structural colors and can be deposited on a variety of substrates relevant to packaging, textiles, cosmetics, and other coating technologies.

Beyond coloration, the nanostructured BCP framework provides a programmable host matrix for the selective incorporation of functional nanomaterials. Quantum dots, plasmonic nanoparticles, and magnetic nanoparticles can be localized within specific polymer domains, producing hybrid microparticles that combine Bragg reflection with photoluminescent, plasmonic, or magnetic functionalities. In this way, optical properties arising from the periodic BCP structure can be coupled with additional responses originating from the incorporated nanomaterials. The emulsion-based processing strategy also allows the construction of more complex hierarchical particle architectures. In particular, double-emulsion templates can be used to generate core-shell microparticles in which a structurally colored BCP shell surrounds a functional liquid or solid core.

Control over droplet deformation and particle morphology further enables the fabrication of anisotropic rod-like photonic microparticles with orientation-dependent optical properties. When magnetic nanoparticles are incorporated, these anisotropic particles can be aligned by external magnetic fields, enabling control of their optical response through particle orientation. Their incorporation into thermoresponsive polymer gels provides an additional route towards reprogrammable photonic materials. In the gel state, the particles are immobilized within the polymer network, preserving their orientation and the corresponding optical state. Upon transition to the sol state, particle mobility is restored, allowing the microparticles to be reoriented under an applied magnetic field. Subsequent gelation fixes the newly programmed orientation, enabling repeated switching between mobile and immobilized states and the reconfiguration of the material's macroscopic optical response.

Overall, confined BCP self-assembly provides a scalable, modular route to structurally colored, multifunctional microparticles. The ability to control internal periodicity, refractive-index contrast, nanoparticle localization, particle shape, hierarchical compartmentalization, and field-induced orientation enables the development of static, responsive, and reprogrammable photonic materials. These capabilities offer opportunities for applications in sensing, optical tagging, anti-counterfeiting, adaptive coatings, display technologies, and wearable photonic devices.

RETHINKING EPOXY THERMOSETS: FROM DYNAMIC NETWORKS TO CIRCULAR MATERIALS

V. Ambroggi

Dipartimento di Ingegneria Chimica, dei Materiali e della Produzione Industriale, Università di Napoli
Federico II, Piazzale Tecchio 80, 80131, Napoli, Italia
e-mail: ambroggi@unina.it

Epoxy thermosets are crucial in high-performance applications owing to their outstanding mechanical properties, thermal stability, and chemical resistance. However, their permanently crosslinked networks poses significant challenges for repair, recycling, and end-of-life management, making them one of the most critical materials in the transition toward a circular economy.

I will discuss the different strategies currently being explored to improve the sustainability of epoxy thermosets. These include the development of vitrimeric epoxy networks as a sustainable-by-design approach, the conversion of conventional thermosets into vitrimer-like ones through mechanochemistry, and the use of solvolysis to recover valuable chemicals by upcycling end-of-life materials. The fundamental principles behind these strategies will be highlighted by discussing representative examples from recent research, and addressing the opportunities and environmental challenges associated with their implementation. Together, they demonstrate how advances in polymer chemistry and technology are opening new perspectives for enhancing the sustainability of epoxy thermosets without compromising the performance that makes these materials essential in demanding applications.

CYCLIC OLEFIN BASED COPOLYMERS VIA TRANSITION METAL CATALYSIS: BRIDGING SYNTHESIS AND FUNCTIONAL APPLICATION

S. Losio

¹ Istituto di Scienze e Tecnologie Chimiche “G. Natta” (SCITEC-CNR), via A. Corti 12, 20133, Milano, Italia
e-mail: simona.losio@cnr.it

Cyclic olefin copolymers (COCs) are thermoplastic materials composed of a cyclic olefin - typically norbornene - and ethylene, generally synthesized via metallocene catalysts [1]. COC exhibit low water absorption, excellent electrical insulation, biological inertness, and UV transparency, making them suitable for advanced biomedical, membrane, and optical applications.

Several commercial COC families exist, differing in monomer structures and polymerization methods. In general, COCs are produced by chain copolymerization of cyclic monomers such as norbornene or

~~TOPAS Adodecane Polymers (for example,~~

manufactures TOPAS COCs from norbornene and ethylene, whereas Mitsui Chemicals utilizes tetracyclododecane to produce APEL COCs. Notably, norbornene monomer synthesis is complex and poses significant engineering safety challenges, which historically led to market monopolies and high manufacturing costs.

While early commercial developments relied on Ziegler–Natta systems, the advent of metallocene and half-sandwich complexes - such as constrained geometry type or non-bridged titanocene-, activated by methylaluminoxane (MAO), revolutionized the field by enabling precise control over polymer microstructure, composition, and transparency [2]. Recent research has expanded beyond traditional formulations to focus on the copolymerization or terpolymerizations of cyclic olefins with propylene, higher α -olefins, functionalized cyclic olefins, reactive dienes to tailor thermal, chemical, and mechanical performances [3]. Understanding the relationships between catalyst design and polymer properties provides key insights into both academic research and industrial applications, facilitating the development and commercialization of advanced COCs with tailored properties [4].

References:

- [1] Tritto, I.; Boggioni, L.; Ferro, D. R. *Coord. Chem. Rev.* **2006**, *250*, 212–241.
- [2] Wang, W.; Qu, S.; Li, X.; Chen, J.; Guo, Z.; Sun, W.-H. *Coord. Chem. Rev.* **2023**, *494*, 215351.
- [3] Losio, S.; Boggioni, L.; Vignali, A.; Bertini, F.; Nishiyama, A.; Nomura, K.; Tritto, I. *Polym. Chem.* **2025**, *16*, 3709–3719.
- [4] Losio, S.; Tritto, I.; Boggioni, L.; Mancini, G.; Luciano, G.; Tofani, L.; Viglianisi, C.; Menichetti, S.; Sacchi, M.C.; Stagnaro, P. *Polym. Degrad. Stab.* **2017**, *144*, 167–175.
- [5] Fredi, G.; Mallegni, N.; Dorigato, A.; Milazzo, M. *Adv. Funct. Mater.* **2026**, *36*, e75610.

FUNCTIONALIZED POLYMERIC MATERIALS: VERSATILE MACROMOLECULAR PLATFORMS FOR PHARMACEUTICAL AND ENVIRONMENTAL APPLICATIONS

Chiara Zagni

Dept. of Drug and Health Sciences, Università di Catania, V.le A. Doria 6, 95125, Catania, Italy

The design of functionalized polymeric materials provides versatile macromolecular platforms capable of addressing critical challenges in both the pharmaceutical and environmental sectors. In pharmaceutical applications, three-dimensional porous networks serve as biocompatible containers for controlled drug delivery and as active heterogeneous supports for metal catalysts (e.g., Pd complexes) in the catalytic synthesis of Active Pharmaceutical Ingredients (APIs). Concurrently, for environmental mitigation, amino acid functionalized surfaces can generate and selectively capture CO₂.

3D PRINTING MEETS LIQUID CRYSTAL POLYMERS: RESPONSIVE MATERIALS ACROSS DIFFERENT SCALES AND APPLICATIONS

C. Parmeggiani^{1,2}, S. Nocentini², D. S. Wiersma³, D. Martella^{1,2}

¹ Department of Chemistry “Ugo Schiff”, University of Florence, Via della Lastruccia 3-13, 50019 Sesto Fiorentino, Italy

² European Laboratory for Non-Linear Spectroscopy (LENS), Via Carrara 1, 50019 Sesto Fiorentino, Italy
e-mail: daniele.martella@unifi.it

The use of light in polymer science offers unique opportunities, spanning from fabrication of smart materials by photopolymerization, to their actuation for different applications. By combining shape-changing liquid crystalline networks (LCNs) with advanced 3D printing technologies, complex architectures with stimuli-responsive properties can be produced. LCNs are crosslinked polymer networks prepared from reactive mesogens that efficiently convert external stimuli, such as light, into mechanical motion. Their chemical composition can be tailored to tune mechanical properties and optimize force generation during actuation. In this contribution, we demonstrate their integration with additive manufacturing techniques to fabricate a variety of functional devices, including light-driven actuators, structurally colored responsive structures, and photonic components.

Polyesters in Water: From Dispersion Strategies to Functional Applications

Matteo Calosi¹, Andrea D'Iorio¹, Elena Buratti², Monica Bertoldo¹

¹ Department of Chemical, Pharmaceutical and Agricultural Sciences, University of Ferrara, Via L. Borsari, 46, 44121 Ferrara, Italy
e-mail: andrea.monica.bertoldo@unife.it

² Department of Environmental and Prevention Sciences, University of Ferrara, C.so Ercole I D'Este, 32, 44122 Ferrara, Italy

Aqueous dispersions of biopolyesters have long been used in drug delivery, typically in highly diluted formulations. At higher solid contents, however, they open new opportunities as sustainable waterborne materials for films, coatings, and functional composites. Our group has developed stable biopolyester dispersions with solid contents up to 40%, suitable for paper coatings that provide water and oil resistance while preserving biodegradability and recyclability. These systems can also be blended with water-soluble polymers such as polyvinyl alcohol, combined with fillers such as graphene oxide for sensor applications, or used to incorporate thermolabile bioactive molecules, including osteogenic peptides in PLA films. Beyond PLA, we are exploring different polyesters, including PLGA obtained from CO

4D-Printable Shape Morphing Double Network Granular Elastomers (DNGEs)

DANIELE NATALI¹, ESTHER AMSTAD¹.

¹ Institute of Materials, Soft Materials Laboratory (SMaL), École Polytechnique Fédérale de Lausanne (EPFL, Switzerland)
email: daniele.natali@epfl.ch

The growing relevance of soft robotics within materials science has, in the recent years, driven increasing interest in the development of soft, yet load-bearing and responsive materials that can be processed into customized shapes. Double network granular elastomers (DNGEs), composed of crosslinked microparticles interconnected through a second interpenetrated elastomeric network combine toughness with load-bearing properties and extrudability.¹ To prepare DNGEs, the microparticles are swollen in the precursors' solution of the second network before being centrifuged to increase packing density of the microparticles to a point where they are named jamming (Figure 1a). In the jammed state, the swollen microparticles are shear-thinning, exhibit a low yield point and fast shape recovery, assets ideal for (DIW)-based 3D printing (Figure 1b). The mechanical properties of DNGEs can be tuned with the composition of the DNGE. In this talk, I will introduce smart DNGEs that exhibit a thermo-sensitive shape-morphing behaviour. This is achieved by formulating DNGEs from crystallizable monomers that are crosslinked through a photo-induced thiol-ene reaction. The crystallization of polymeric domains are exploited for the fixation of different temporary shapes, while the original shape of samples is recovered by heating above the material's melting transition (Figure 1c). Semicrystalline domains thus consent to combine the enhancement of the mechanical properties with the obtainment of thermo-sensitive shape-memory properties, introducing a novel elastomeric material suitable for load-bearing applications and capable to generate active force upon heating (Figure 1d). Mechanical properties of the DNGEs are optimized by regulating the amount of crosslinker in the microparticles and in the second network. Leveraging multi-material DIW printing, I will showcase DNGEs with locally varying compositions that deform in pre-defined ways. I foresee shape-memory DNGEs, to open up new possibilities in 4D-printing load-bearing smart materials well-suited, for example for soft robotics.




Figure 1. a) steps for the preparation of the shear-thinning ink: first the microparticles are swelled in the solution of second network precursors before being jammed; b) flow curve of the ink showing shear-thinning behavior; c) shape-memory properties of 3D-printed DNGEs; d) load-bearing and active force demonstration of shape-morphing DNGEs: the materials can be programmed to bear and lift loads when activated through heating.

References:

[1] E. Baur, B. Tiberghien, E. Amstad. Advanced Materials. 3D Printing of Double Network Granular Elastomers with Locally Varying Mechanical Properties, 36, 2313189, 2024.

Altri
CONTRIBUTI ORALI

Altri
CONTRIBUTI ORALI

Polimeri da fonti
rinnovabili e
degradabili, riciclo

DEVELOPMENT OF ACTIVE BIODEGRADABLE PLA/PBSA FILMS CONTAINING BLUEBERRY WASTE ANTIOXIDANTS EXTRACTED USING NADES AS GREEN SOLVENTS

A. Barbato¹, F. Alchera², L. Incarnato¹, A. Apicella¹

¹ Department of Industrial Engineering, University of Salerno, via Giovanni Paolo II 132, 84084 Fisciano (SA), Italy

² Department of Chemistry, University of Turin, Via Pietro Giuria 5, 10125, Turin (TO), Italy
e-mail: abarbato@unisa.it

Biodegradable active packaging represents a promising strategy to improve food preservation while reducing environmental impact. In this work, antioxidant compounds recovered from blueberry peels using Natural Deep Eutectic Solvents (NADES) were incorporated into PLA-based coatings applied onto biodegradable PBSA/PLA films. The extracts and resulting films were characterized for antioxidant activity, physicochemical, optical, mechanical, barrier and release properties. The selected extract provided antioxidant functionality while preserving suitable packaging performance. Release tests confirmed the potential of the films as active carriers for food-contact applications. Ongoing shelf-life tests on fresh-cut fruit are being carried out under refrigerated storage conditions.

MULTIFUNCTIONAL EUGENOL-BASED NANOGELS THROUGH COPOLYMER DESIGN: ANTIOXIDANT ACTIVITY, INTRINSIC FLUORESCENCE, AND DRUG ENCAPSULATION

Benedetta Brugnoli¹, Alessia Mariano^{2,3}, Valerio La Gambina¹, Daniel Salzarulo¹, Mauro Giustini¹, Luisa M. Migneco¹, Antonella Piozzi¹, Anna Scotto d'Abusco², Alessandra Del Giudice¹, Luciano Galantini¹, Karin Schillén⁴, Claudia Vuotto⁵, Jonathan D. Hirst⁶, Dmitry Karlov⁶, Vincenzo Taresco⁶, Iolanda Francolini¹

¹ Department of Chemistry, Sapienza University of Rome, Piazzale Aldo Moro, 00185, Rome, Italy

² Department of Biochemical Sciences, Sapienza University of Rome, Rome, Italy

³ BeSSA Department, Wellbeing, Health and Environmental Sustainability, Sapienza University of Rome, Via delle Fontanelle snc, Rieti, Italy

⁴ Department of Chemistry, Lund University, P.O. Box 124, Lund SE-22100, Sweden

⁵ Saint Camillus International University of Health Sciences, Via di Sant'Alessandro, 8, 00131, Rome, Italy

⁶ School of Chemistry, University of Nottingham, University Park, NG7 2RD, Nottingham, United Kingdom
e-mail: benedetta.brugnoli@uniroma1.it

Amphiphilic nanogels were synthesized by dispersion copolymerization of an eugenol-based methacrylate (EUMA) and hydroxyethyl methacrylate (HEMA). Preserving the phenolic moiety of eugenol enabled a single-motif design with intrinsic antioxidant and antimicrobial activities. Dynamic Light Scattering (DLS) showed nanogels with sizes between 80–210 nm, with higher EUMA content promoting more compact structures. Notably, the nanogels exhibited intrinsic pH-dependent fluorescence (420 nm), attributed to oxidative coupling of eugenol units, enabling self-reporting behavior without external dyes. Encapsulation of usnic acid (UA) significantly improved its aqueous solubility and reduced *in vitro* cytotoxicity while preserving antibacterial activity against Gram-positive bacteria.

SOLVENT-FREE GRAFTING OF PBS OLIGOMERS ONTO CELLULOSE NANOFIBERS FOR ENHANCED BIOCOMPOSITE COMPATIBILITY

Andrea D'Iorio¹, Simone Fantinel¹, Elena Buratti², Giulia Ronconi³, Lucia Gioiella⁴,
Giuseppe Proietto Salanitri⁵, Monica Bertoldo¹.

¹ Department of Chemical, Pharmaceutical and Agricultural Sciences, University of Ferrara, Via L. Borsari, 46, 44121 Ferrara, Italy

e-mail: andrea.diorio@unife.it

² Department of Environmental and Prevention Sciences, University of Ferrara, Via L. Borsari 46, Ferrara 44121, Italy

³ Department of Engineering, University of Ferrara, Via Saragat 1, 44122 Ferrara, Italy

⁴ Department of Chemical, Materials and Production Engineering (INSTM Consortium – UdR Naples), University of Naples Federico II, Piazzale Tecchio 80, Naples 80125, Italy

⁵ Institute for Polymers, Composites and Biomaterials CNR-IPCB, Via Paolo Gaifami 18, 95126 Catania, Italy

Nanocellulose, especially cellulose nanofibers (CNFs), is of great interest due to its excellent mechanical properties, low density, non-toxicity, and thermal stability. However, its high hydrophilicity limits its applications. To address this issue, CNFs were chemically modified through a three-step process: 1) oxidation of cellulose fibers; 2) mechanical extraction of CNFs; 3) solvent-free grafting of poly(butylene succinate) (PBS) oligomers onto the cellulose chains. The grafting process used succinic acid and 1,4-butanediol while evaluating different catalysts, temperatures, and reaction times. The results confirmed successful PBS grafting, offering promising prospects for investigating the incorporation of these modified CNFs into PBS polymer matrices to develop sustainable polymer composites.

MECHANOCHEMICAL POLYMER-TO-POLYMER RECYCLING OF POLYLACTIC ACID

A. Kiani,¹ A. Di Martino,¹ F. Santulli,¹ M. Carratù,¹ M. Mazzeo,¹ M. Rosaria Acocella¹ (underline the corresponding author)

¹ Department of Chemistry and Biology "A. Zambelli", University of Salerno, Via Giovanni Paolo II, 132-84084 Fisciano (SA)- ITALY

Mechanochemistry represents a promising sustainable approach for polymer recycling, enabling chemical transformations through mechanical. In this work, a solvent-free and catalyst-free strategy for the closed-loop recycling of poly(lactic acid) (PLA) is presented. By tuning ball-milling parameters, controlled radical-induced depolymerization of PLA with different molecular weights was achieved, yielding low-molecular-weight oligomers. Remarkably, further adjustment of milling time promoted the in situ repolymerization of these species, restoring molecular weights comparable to those of the pristine polymer. The entire process occurs in the solid state and relies exclusively on mechanical activation. This approach provides a sustainable alternative for PLA end-of-life management and demonstrates the potential of mechanochemistry for circular polymer recycling.

(Meth)-acrylated tannic acid as a bio-based adhesion promoter for EB-curable coatings

F.Bisio¹, K.Sparnacci¹, G.Mirone², S.Pasquin², A.Nicorelli²

¹ Dipartimento di Scienze ed Innovazione Tecnologica,
Università degli Studi del Piemonte Orientale "A.
Avogadro" via Michel 11, 15121 Alessandria, Italy
e-mail: katia.sparnacci@uniupo.it

.....
² METLAC SpA, Strada Provinciale ex strada statale 35 Bis
Dei Giovi 53, 15062 Bosco Marengo, AL, Italy

Electron beam (EB) curing is a solvent-free, energy-efficient technology for advanced coatings that enables photoinitiator-free polymerization, thereby minimizing extractable species. This study investigates partially acrylated tannic acid derivatives as bio-based adhesion promoters for EB-curable acrylic coatings in metal food packaging. The additives were incorporated at varying concentrations and evaluated on metal substrates. The results demonstrated enhanced adhesion, flexibility, and resistance to corrosion-induced delamination, particularly at an optimal loading of 1.0 wt%. These findings highlight the significant potential of combining EB curing with bio-based additives to develop sustainable, high-performance coatings for food packaging applications.

ENVIRONMENTALLY FRIENDLY UPCYCLING OF PHA-BASED COPOLYMERS INTO BRANCHED MULTIFUNCTIONAL OLIGOMERS

G. Damonte¹, M. Cozzani¹, A. Fortunato¹, A. Pellis¹, G. M. Guebitz^{2,3}, O. Monticelli¹

¹Università degli Studi di Genova, Dipartimento di Chimica e Chimica Industriale, Via Dodecaneso 31, 16146 Genova, Italy

²Institute of Environmental Biotechnology, Department of Agricultural Sciences, BOKU University, Konrad-Lorenz-Strasse 20, 3430 Tulln an der Donau, Austria

³Austrian Centre of Industrial Biotechnology, Konrad-Lorenz-Strasse 20, 3430 Tulln an der Donau, Austria
e-mail: giacomo.damonte@edu.unige.it

This study addresses two fundamental aspects that make the use of bioplastics sustainable and circular, namely their recycling and valorization of the products resulting from this process. Following this rationale, poly(3-hydroxybutyrate-co-3-hydroxyhexanoate) (PHBH) was upcycled through a green solventless approach to functional oligomers having branched structures. The developed oligomers were used as additives to impart functionality to porous films based on the starting high molecular weight PHBH, prepared by exploiting a phase inversion method using Cyrene®, a solvent derived from cellulose. The developed films were tested in terms of water and ion retention, showing promising results. Moreover, enzymatic hydrolysis of the systems using *Humicola insolens* Cutinase at different concentrations and in different media was investigated.

AMORPHOUS BLENDS OF PLA AND PHA FOR WATERBORNE COATINGS AND FOAM APPLICATIONS

M. Calosi¹, A.D'Iorio¹, C. Raouf^{1,2}, M. Lahcini², M. Dippold³, H. Ruckdäschel³, E. Buratti⁴, M. Bertoldo¹

¹ Department of Chemical, Pharmaceutical and Agricultural Sciences, University of Ferrara,
via Borsari 46, 44121 Ferrara, Italy

² IMED-Lab, Faculty of Sciences and Techniques, Cadi Ayyad University, Avenue Abdelkrim Elkhattabi,
B.P. 549, 40000 Marrakech, Morocco

³ Department of Polymer Engineering, University of Bayreuth, Universitätsstraße 30, 95447, Bayreuth,
Germany

⁴ Department of Environmental and Prevention Sciences, University of Ferrara,
via Borsari 46, 44121 Ferrara, Italy

This study presents a strategy to overcome the limited environmental biodegradability of poly(lactic acid) (PLA) by blending it with an amorphous polyhydroxyalkanoate (PHA). Two processing routes were explored: waterborne dispersion—used to create paper coatings and free-standing films—and melt-compounding, utilized for producing low-density foams via supercritical CO₂ foaming. Despite the inherent immiscibility of the two polymers, the blends demonstrated excellent processability by both techniques. Crucially, the addition of PHA accelerated the biodegradation of the PLA phase under home-composting conditions. A 30% PHA content found to achieve home-compostable status for films, while foams exhibited slower degradation.

INVESTIGATION INTO THE POTENTIAL OF POLY(β -AMINO ESTER)- BASED VITRIMERS

Riccardo Chiarcos¹, Mattia Lippelli¹, Diego Antonioli¹, Michele Laus¹

¹ Dipartimento di Scienze e Innovazione Tecnologica, Università del Piemonte Orientale (UPO), Viale T. Michel 11, 15121, Alessandria, Italia
e-mail: riccardo.chiarcos@uniupo.it

Vitrimer materials are crosslinked networks containing dynamic covalent bonds that, in the presence of appropriate stimuli, allow the material to flow, making it reprocessable. Among the various types of vitrimers, one of the most promising system consists of poly(β -amino ester)s synthesized by the Aza-Michael reaction of acrylate and amine monomers. In this communication, poly(β -amino ester)s synthesized using different amounts of both bifunctional and trifunctional acrylates will be presented. The influence of the trifunctional acrylate on the thermal and reprocessing properties of the materials will be discussed. Furthermore, an innovative reprocessable system based on poly(β -amino ester)s oligomers cured by radical polymerization with a methacrylic monomer will be presented.

FORMULATION AND CHARACTERIZATION OF POLYHYDROXYALKANOATE BLENDS WITH WASTE PROTEIN FIBERS FOR PACKAGING APPLICATION

S. Alfano¹, G. Tittaferante¹, A. Martinelli¹, A. Piozzi, L. Galantini¹, R. Mezzenga², I. Francolini¹

¹ Dept. of Chemistry, Università di Roma La Sapienza, Piazzale Aldo Moro 5, 00185, Roma, Italy

² Dept. of Health Sciences & Technology, ETH Zurich, Schmelzbergstrasse 9, 8092, Zurich, Switzerland
e-mail: sara.alfano@uniroma1.it

This study explores a sustainable strategy to develop polyhydroxyalkanoate-based blends for flexible packaging applications. A tailored compatibilization approach, involving the synthesis of sulfonated PHBH (PHBH-SO₃) as compatibilizer, was investigated to improve the integration of functional components derived from agri-food waste within the hydrophobic PHBH. Thermal characterization of the resulting materials, processed into films by conventional compression molding, indicates an effect of the incorporated bio-based phase on polymer crystallization, presumably acting as a nucleating agent. Contact angle measurements confirmed the retention of PHBH hydrophobic behaviour. Ongoing mechanical and viscoelastic assessments will further evaluate their potential as sustainable alternatives for flexible packaging

DEVELOPMENT AND INDUSTRIAL PROCESSING OF CELLULOSE-BASED MATERIALS FOR RIGID PACKAGING APPLICATIONS

A.Giovagnoli¹, L. Menegaldo², F. Bonvicini², D. Caretti¹, G. Mazzotti³

¹ Dept. of Industrial Chemistry "Toso Montanari", University of Bologna, Via P. Gobetti 85, 40129, Bologna, Italy

² Dept. of Pharmacy and Biotechnology, University of Bologna, Via Massarenti 9, 40138, Bologna, Italy

³ SACMI S.C., Via Selice 17/A, 40026, Imola, Italy

e-mail: angelica.giovagnoli2@unibo.it

In this research project fully cellulose-based materials through bio-derived functional additives application and industrial processing of the cellulosic material have been developed. The synthetic additives were applied onto cellulose substrates by spray coating methodology and moulded into three-dimensional objects, bottle's cap and bottle-neck shaped by dry compression moulding technology. The resulting materials showed excellent water barrier performance and biologically active properties. Structural, thermal, and mechanical characterization confirmed integrity and suitability for rigid packaging applications.

USE OF FRUIT PEELS FOR THE DEVELOPMENT OF BIO-BASED HYDROGELS

D. Gaikwad, M. Mauri, U. Edlund, R. Simonutti

³ Dept. of Fibre and Polymer Technology , Royal Institute of Technology KTH, Teknikringen 56, 10044 Stockholm, Sweden

⁴ Dipartimento di Scienza dei Materiali;Università di Milano – Bicocca;Via Cozzi 55, Milano, Italy

Email: d.gaikwad@campus.unimib.it

This work presents a bio-based semi-interpenetrating hydrogel for wastewater treatment, derived from agricultural biomass such as green kiwi and green apple peels. The gel network was formed through free radical polymerization using HEMA and PEGMA chains crosslinked with N,N-methylene-bis(acrylamide), in presence of cellulose, hemicellulose, and the other main components of the dried peel. Methylene blue was used to evaluate adsorption performance and network stability with hydrogel based on Green kiwi peels, while green apple gel was also tested with diclofenac sodium (DCF), a non-steroidal anti-inflammatory drug, and norfloxacin (NOR), a fluoroquinolone antibiotic. The results indicate that fruit-peel-based hydrogels can maintain their polymer network while showing promising adsorption capacity toward dye and drug molecules.

N. Victoria dos Santos¹, L. Gioiella¹, V. Ambrogio¹, M. Salzano de Luna¹, G. Filippone¹

¹ Dipartimento di Ingegneria Chimica, dei Materiali e della Produzione Industriale (DICMaPI), Università di Napoli Federico II, p. le Tecchio 80, 50125, Napoli, Italia

e-mail: gfilippo@unina.it

Short-fiber thermoplastic biocomposites combine the processability of thermoplastics with the improved end-of-life options of bio-based matrices and natural fibers. Their mechanical performance strongly depends on the fiber–matrix interfacial shear strength (τ_y), commonly measured by pull-out tests. However, pull-out specimens are often prepared without pressure, whereas pressure is always present during composite manufacturing. As a result, measured τ_y values may not reflect real processing conditions. Here, we investigate the pressure dependence of τ_y in a PLA–hemp model system, showing that τ_y markedly increases with specimen-preparation pressure due to enhanced matrix penetration into hemp-fiber surface roughness, which increases the effective fiber–matrix contact area.

STRUCTURAL CONTROL AND AMYLOID REINFORCEMENT OF WASTE-DERIVED PROTEIN FILMS

M. Colombo¹, E. Testa¹, E. Fasoli¹, D. Gentile¹, V. Barbera¹, M. Galimberti¹

¹ Department of Chemistry, Materials and Chemical Engineering "G. Natta", Politecnico di Milano, Via E. Bassini 6, 20131 Milano, Italy

Bioplastic films were developed through the valorization of waste proteins from black soldier flies (BSFs) and sericin. Following proteomic characterization, the films were prepared and their properties were correlated with the structure of the proteins. Higher molecular mass and transitions towards β -sheet architectures were found to significantly improve mechanical performance. Protocols specific to the proteins were developed for amyloid fibrillization, which further enhanced the properties of the films in both pure protein systems and blends with biodegradable polymers. Lyophilised amyloid-containing proteins were also used as nanofillers to reinforce biodegradable polymer matrices. Overall, amyloid fibrillization proved to be an effective strategy for producing protein-based materials with properties comparable to those of commercially available biopolymers.

PROSPECTIVE LIFE CYCLE ASSESSMENT OF TYRE MANUFACTURING: EVALUATING INDUSTRIAL DECARBONISATION PATHWAYS

V. La Matta¹, V. Ambrogio¹, M. Salzano de Luna¹, G. Filippone¹

¹ Department of Chemical, Materials and Production Engineering, University of Naples Federico II, P.le
Tecchio 80, 80125, Napoli, Italy
e-mail: valentina.lamatta@unina.it

(INSERIRE UN ABSTRACT DI NON PIU' DI 8 RIGHE)

The tyre industry is progressively shifting towards renewable and recycled materials, with leading manufacturers targeting approximately 40% sustainable material content by 2030. This work uses a cradle-to-gate Life Cycle Assessment (LCA) of a representative passenger car tyre, developed from primary industrial production data, as the baseline for prospective decarbonisation scenarios based on current industrial sustainability roadmaps. Alternative strategies are assessed through comparative LCA to quantify their potential for reducing the environmental footprint of tyre manufacturing and to identify the most promising material-oriented decarbonisation pathways.

FROM THIOL-ENE CHEMISTRY TO BIO-BASED POLYMERIC NETWORKS: MULTIFUNCTIONAL LIMONENE-DERIVED MATERIALS

N. Ferrentino^{1,2}, G. Viscusi², D. Pappalardo¹, G. Gorrasi².

¹ Department of Sciences and Technologies, University of Sannio, via de Sanctis snc, 82100, Benevento, Italy.

² Department of Industrial Engineering, University of Salerno, via Giovanni Paolo II 132, Fisciano, 84084, Italy.

e-mail: naferrentino@unisannio.it

Limonene, an abundant terpene derived from citrus waste, and limonene epoxide were exploited through thiol-ene chemistry to produce two complementary classes of bio-based materials. First, linear and branched thiols were used to prepare poly(thioether-co-limonene) networks, which were combined with recycled poly(vinyl butyral) (PVB) to obtain materials with enhanced mechanical properties and excellent UV-shielding performance. The same thiol chemistry was applied to limonene epoxide to prepare multifunctional epoxy precursors, which were cured with bio-based di- and tricarboxylic acids to obtain epoxy resins. Overall, the results highlight the versatility of thiol chemistry as a sustainable strategy for developing multifunctional polymers from renewable resources and recycled materials.

EMERGING CONCEPTS FOR SUSTAINABLE BIOCOMPOSITES

C. Di Bernardo¹, C. Noè¹, M. Messori¹

¹ Dept. of Material Science and Technology, Politecnico di Torino, Corso Duca degli Abruzzi, 24, 10128, Torino (TO), Italy

.....
e-mail: carlo.dibernardo@polito.it

The transition toward a circular bioeconomy is reshaping polymer composite design, promoting materials that combine high performance with sustainability. Recent advances span traditional composites, dynamic covalent networks, and hydrogel-based systems. Biocomposites are evolving from static structures to adaptive, multifunctional materials integrating renewable matrices and bio-based fillers. In tire applications, biochar can replace up to 50% of carbon black while maintaining comparable properties. Covalent adaptable networks based on Priamine® 1071 provide reprocessible, flexible matrices with rapid stress relaxation, suitable for soft strain-sensing composites. In parallel, photocurable collagen hydrogels offer biomimetic, porous platforms for biomedical and absorbent applications. Overall, current research emphasizes the convergence of bio-derived feedstocks, dynamic chemistries, multifunctionality, and circularity as key directions for next-generation biocomposites.

TUNING PLLA CRYSTALLIZATION KINETICS VIA REACTIVE EXTRUSION BRANCHING STRATEGIES

A. Longo¹, M. L. Di Lorenzo¹, A. Staiano¹, V. Marturano¹, G. Dal Poggetto¹, S. Mallardo¹,
M. Dobrzyńska-Mizera², Monika Knitter², Karol Bula², Agnieszka Kuc²

¹ Istituto per i Polimeri, Compositi e Biomateriali (IPCB); Consiglio Nazionale delle Ricerche (CNR), Via
Campi Flegrei 34, 80078, Pozzuoli, Italia

² Institute of Materials Technology, Division of Plastic Processing, Poznan University of Technology,
Piotrowo 3, 61-138 Poznan, Poland.

e-mail: alessandra-longo@cnr.it

Poly (L-lactic acid) (PLLA) a diffused biodegradable and renewable thermoplastic polyester with a few drawbacks that limit its wider commercial exploitation. A major limitation hindering the large-scale industrial application PLLA is its slow crystallization kinetics, which results in brittle behavior and poor thermal resistance.

This contribution presents the synthesis of long-chain branched PLLA via reactive extrusion. The synthesized branched PLLAs exhibited enhanced crystal nucleation with a strong concentration-dependent effect. This strategy provides a robust approach to overcome the performance bottlenecks of commercial PLLA, expanding its viability for high-performance sustainable packaging and engineering applications.

DESIGNING VANILLIN-BASED DYNAMIC NETWORKS FOR THE DEVELOPMENT OF SUSTAINABLE THERMOSETS FOR FUTURE GENERATION COMPOSITES

M. Mollo¹, C. Noè¹, and M. Messori^{1,2}

¹ Department of Applied Science and Technology (DISAT), Politecnico di Torino, C.so Duca degli Abruzzi 24, 10129, Turin (TO), Italy

² National Interuniversity Consortium of Materials Science and Technology (INSTM), Florence (FI), Italy
e-mail: marta.mollo@polito.it

The present work contributes to the optimization of traditional thermosets, aiming to overcome the challenge of their poor recyclability while preserving excellent thermal and mechanical properties for high-performance applications. Two distinct formulations were developed, using vanillin as a competitive building block compared to fossil-based analogues and a dynamic cross-linked network that can be reprocessed when stimulated by heat. Once the vitrimeric behaviour was assessed, further tests were performed to investigate advanced functionalities of these materials. The higher T_g thermoset exhibited no chemical degradation along with promising flame resistance properties. On the other hand, the lower T_g formulation was investigated as a smart material demonstrating outstanding shape memory behaviour.

MELT-PROCESSING OF DIALCOHOL CELLULOSE FIBRES/STARCH BLENDS: PROCESSING STRATEGIES, STRUCTURE AND PROPERTIES

Enrica Pellegrino^{1,2}, Giada Lo Re², Alberto Fina¹

¹Politecnico di Torino, Dipartimento di Scienza Applicata e Tecnologia, viale Teresa Michel 5, 15121
Alessandria, Italy

²Chalmers University of Technology, Department of Industrial and Materials Science, Rännvägen 2A, 412
58 Göteborg, Sweden

Growing concerns about fossil-based plastics have driven interest in renewable alternatives like cellulose and starch-based polymers. However, their strong hydrogen bonding intermolecular interactions raise glass transitions above degradation temperatures, which hinders melt-processing. Chemical modification of cellulose into dialcohol cellulose fibres (DALC) reduces glass transition, enabling water assisted melt-processing. Starch can also be melt-processed using suitable plasticizers, such as isosorbide. DALC/starch blends were produced using either a one-step co-extrusion process or a two-step process involving pre-formed thermoplastic starch pellets. Higher starch content reduced melt-viscosity, improving processability. The blend composition and processing route influence the mechanical properties. Selected compositions demonstrated successful mechanical recycling and composting biodegradation, confirming the potential of these bio-based thermoplastic alternatives.

Beyond Biodegradability: Comparative LC-MS Profiling of Plastic Additive Release from Fossil-Based and Biodegradable Agricultural Mulch Films into Soil

V. Giglio¹, F. Convertino², E. Schettini², S.C. Carroccio¹

¹ Institute for Polymers, Composites, and Biomaterials CNR-IPCB, Via Paolo Gaifami 18, Catania 95126, Italy

e-mail: valentina.giglio@cnr.it

² Department of Soil, Plant and Food Sciences (DISSPA), University of Bari, Via Amendola 165/A, Bari 70126, Italy

Biodegradable mulch films (BMF) are promoted as eco-friendly alternatives to polyethylene (PE), yet both contain plastic additives (PAs) that can leach into agricultural soil during burial. This study presents a comparative UHPLC-MS/MS investigation of PA profiles in PE and PBAT films and contacting soils under real field conditions. PE remained intact with stable PA content throughout burial, while PBAT progressively degraded, releasing micro- and nanoplastics and showing significant PA compositional changes. Hydrophobic PAs persisted in plastic fragments; polar species migrated preferentially into soil. These findings show that polymer biodegradability does not ensure reduced environmental impact of associated additives, urging inclusion of their fate in sustainability assessments of agricultural plastics.

MULTISCALE POLYMER ANALYSIS: CORRELATING CHEMICAL STRUCTURE, THERMAL BEHAVIOR, AND RHEOLOGICAL RESPONSE THROUGH COMPLEMENTARY ANALYTICAL TECHNIQUES

Alberto Rubin Pedrazzo¹, Carmine Invigorito¹, Sandra Lanteri¹, Paolo Saccagno¹,
Simone Marchesi¹

¹ Anton Paar Italia Srl, Via Albenga, 78, 10098 Rivoli (TO), Italia
e-mail: alberto.rubinpdrizzo@anton-paar.com

Polymer properties arise from structural features extending from the molecular to the macroscopic scale. This contribution presents an integrated approach combining XRD, DSC, gas pycnometry, Raman, and SAXS. XRD, DSC, and pycnometry provide complementary information on crystalline phases, thermal transitions, crystallinity, and skeletal density. Raman spectroscopy enables real-time monitoring of structural evolution during polymer processing, while RheoSAXS correlates nanoscale organization with rheological response. Selected examples include polypropylene crystallinity, polyethylene crystallization, and shear-induced transitions in lamellar systems. The combined workflow improves structure–process–property understanding and supports material development and process optimization.

WHEN MOLECULAR IMPERFECTION WORKS: SUSTAINABLE POLYESTER COPOLYMERS WITH INDUSTRIAL POTENTIAL

Licia Gaeta¹, David H. Lamparelli¹, Luciano Di Maio,² Claudio Pellecchia¹

¹ Dipartimento di Chimica e Biologia "A. Zambelli", Università degli Studi di Salerno, via Giovanni Paolo II

² Dipartimento di Ingegneria Industriale, Università degli Studi di Salerno, via Giovanni Paolo II 132, Fisciano (SA) 84084, Italy

e-mail: dlamparelli@unisa.it

ABSTRACT

Sustainable ABA segmented copolyesters based on commercially available ϵ -caprolactone and L-lactide were synthesized through a scalable one-pot bulk polymerization using technical-grade monomers and industrially relevant catalysts. Despite the structural heterogeneity generated under these conditions, the materials retained typical thermoplastic elastomer behavior, combining high extensibility with efficient energy dissipation and elastic recovery. Moreover, they proved highly effective as PLA toughening agents, increasing the strain-at-break of commercial PLA from about 4% to over 90% while maintaining technologically relevant mechanical properties. These results demonstrate the potential of scalable polyester architectures for high-performance and recyclable PLA-based materials.

BIO-BASED AND ANTIFUNGAL BY DESIGN: UV-CURED ESO/ESSENTIAL OIL COMPOSITES FOR NEXT-GENERATION ACTIVE PACKAGING

M. Valentini¹, I. Khomenko², E. Betta², M. Tonezzer³, J. Zhang^{1,2,3}, F. Biasioli², A. Cosola¹, C. Noè^{1*}, M. Messori¹

¹Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy;

²Sensory Quality Unit, Research and Innovation Centre, Fondazione Edmund Mach, Trento, Italy

³Department of Chemical and Geological Sciences, University of Cagliari, Monserrato, Italy
e-mail: camilla.noe@polito.it

We engineered a novel device blending natural essential oils (EOs) into a cationically UV-cured epoxidized soybean oil (ESO) matrix, targeting food shelf-life extension and waste reduction. Photo-rheology and ATR-FTIR showed EO loading delays crosslinking onset yet speeds gelation, thus reducing the final epoxy-group conversion from 81% to 70%. DMTA analysis revealed an induced EOs plasticizing effect leading to the formation of samples with lower T_g and storage modulus. PTR-ToF-MS and GC-MS tracked EO release kinetics and oxidation VOC byproducts released by the samples stored at 6, 20 or 35°C. As a proof of concept, antifungal tests against *Penicillium spp.* confirmed real-world applicability. Together, these results spotlight ESO-based UV-cured systems as a sustainable, high-performance route to next-gen active packaging.

NATURAL ANTIOXIDANT EFFECT OF HAZELNUT SHELL POWDER IN PBS BIOCOMPOSITES UNDER ACCELERATED UV AGING

L. Vitiello¹, S.C. Carroccio¹, L. Aliotta², V. Gigante², B. Dal Pont³, J. Passaro³,
P. Russo³

¹ Institute for Polymers, Composites and Biomaterials, National Research Council, Via P. Gaifami 18,
95126, Catania, Italy

² Department of Civil and Industrial Engineering, University of Pisa, Via Lucio Lazzarini, 56122, Pisa, Italy

³ Institute for Polymers, Composites and Biomaterials, National Research Council, Via Campi Flegrei 34,
80078, Pozzuoli (NA), Italy
e-mail: pietro.russo@cnr.it

PBS biocomposites containing 10, 20 and 30 wt.% hazelnut shell powder were subjected to accelerated UV aging in a QUV chamber for up to 90 days. Molecular changes before and after aging were investigated by SEC and MALDI-TOF mass spectrometry. SEC analyses showed that the reduction in number-average molecular weight after 90 days decreased with increasing filler content, while neat PBS exhibited the largest increase in polydispersity. MALDI-TOF results confirmed a lower extent of molecular degradation in the filled systems. The enhanced photo-oxidative stability is likely due to the preferential oxidation of polyphenols in hazelnut shells, acting as sacrificial antioxidants. Mechanical testing also supported the effectiveness of hazelnut shell powder as a sustainable UV-stabilizing filler.

Mechanical Recycling of Multi Coupled Material Body Seals Based on Thermoplastic Elastomers in the Automotive Industry

F. Cano¹, G. Brocani², S. Ponti², G. Ciaccio², V. Brunella¹

¹ University of Turin, Department of Chemistry, Via P. Giuria 7, Turin, 10125, Italy

⁴ Stellantis, C.so Agnelli 220, Turin, 10135, Italy

e-mail: flavia.cano@unito.it

The growing demand for sustainable materials has increased interest in Thermoplastic Elastomers (TPEs) for automotive applications due to their recyclability and elasticity. This work investigates the mechanical recycling of post-industrial multi-material sealing profiles without prior separation. The recycled material was reprocessed and characterized before and after ageing. Mechanical tests showed good hardness, tensile, tear, and compression set properties. Thermal ageing had a limited effect on performance. UV exposure caused only minor degradation and color variation. TGA, DSC, and ATR-FTIR confirmed the material's compositional stability. These results demonstrate the feasibility of recycling complex TPE-based sealing systems for circular automotive applications.

EUGENOL-DERIVED POLYMERIC NETWORKS AS ECO-FRIENDLY AND CIRCULAR WET-STRENGTH AGENTS FOR HIGH-PERFORMANCE PAPER PRODUCTS

R. Sergi¹, C. Negrell², S. Caillol², A. Piozzi¹, A. Martinelli¹, F. Rea³, P. Di Cosimo³, D. Caschera⁴, L. Galantini¹, I. Francolini¹

¹ Department of Chemistry, Sapienza University of Rome, Piaz.le Aldo Moro 5, 00185, Rome, Italy.

² Institut Charles Gerhardt UMR 5253–CNRS, UM, ENSCM, 8 rue de l'Ecole Normale, F-34296 Montpellier Cedex 5, France

³ Gima Water & Air s.R.l (GWA), Via Fratta Rotonda Vado Largo, 03012 Anagni, Italy

⁴ *Institute for the Study of Nanostructured Materials, ISMN-CNR, 00016 Monterotondo Stazione, Roma, Italy*

e-mail: riccardo.sergi@uniroma1.it

This study introduces sustainable alternatives to toxic synthetic paper wet-strength agents by developing novel eugenol-derived polymeric systems. Two routes were investigated: a solvent-free homopolymerization and a radical thiol-ene click copolymerization subsequently photo-crosslinked in situ. When impregnated into cellulose substrates, these green networks successfully imparted robust hydrophobic properties and established continuous fiber bridges that closely mimic the natural moisture-shielding function of lignin. Tensile testing confirmed significant enhancements in wet mechanical strength and overall resilience, successfully matching industrial benchmarks.

ENGINEERING CIRCULAR POLYESTERS THROUGH MOLECULAR ARCHITECTURE: FROM THERMOPLASTIC ELASTOMERS TO DYNAMIC COVALENT NETWORKS

Licia Gaeta¹, Camilla Noè², Maria Gentile¹, David H. Lamparelli¹, Michele Gammino³, Roberto Scaffaro³, Luciano Di Maio,⁴ Claudio Pellecchia¹

¹ Dipartimento di Chimica e Biologia "A. Zambelli", Università degli Studi di Salerno, via Giovanni Paolo II 132, Fisciano (SA) 84084, Italy

² Dipartimento di Scienza Applicata e Tecnologia, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129 Torino, Italy

³ Dipartimento di Ingegneria, Università degli Studi di Palermo, Viale delle Scienze, 90128 Palermo, PA, Italy

⁴ Dipartimento di Ingegneria Industriale, Università degli Studi di Salerno, via Giovanni Paolo II 132, Fisciano (SA) 84084, Italy

e-mail: cpellecchia@unisa.it

ABSTRACT

We used molecular architecture to design bio-based, circular polyester materials, including thermoplastic elastomers and dynamic polymer networks. Using Fe catalysts, ABA triblock copolymers were synthesized with semicrystalline PLLA hard segments and soft amorphous midblocks. These synthetic methodologies proved scalable under industrially relevant conditions using more common monomers and catalysts, yielding more heterogeneous architectures that however act as highly effective toughening agents, increasing commercial PLA's strain-at-break from 4% to over 90%. The study also introduces bio-based vitrimers from star-shaped PLA oligomers, offering shape-memory behavior and stress relaxation. Ultimately, these architectures enable material circularity via efficient depolymerization and chemical recycling.

Altri
CONTRIBUTI ORALI

Materiali polimerici
ibridi e
(nano)compositi
sintesi,
caratterizzazione e
applicazioni

Transparent self-extinguishing silica-epoxy nanocomposites based on Novolac resin

A. Bifulco¹, S. Lehner², A. Arpaia¹, J. Passaro³, P. Russo³, A. Aronne¹, S. Gaan²

¹ Department of Chemical, Materials and Production Engineering (DICMaPI), University of Naples Federico II, P.le Tecchio 80, 80125 Naples, Italy
e-mail: aurelio.bifulco@unina.it

² Laboratory for Advanced Fibers, Empa Swiss Federal Laboratories for Materials Science and Technology, Lerchenfeldstrasse 5, 9014 St. Gallen, Switzerland

³ Institute of Polymers, Composites and Biomaterials (IPCB), National Research Council (CNR), Via Campi Flegrei 34, 80078, Pozzuoli (NA), Italy

Sol-gel chemistry was used to synthesize transparent fire-resistant silica-epoxy nanocomposites based on Novolac resin. Unlike conventional systems, this approach forms well-dispersed amorphous silica nanoparticles, maintaining high transparency (~80% transmittance). A small amount of phosphorus-based additive allows to achieve self-extinguishing without any dripping and achieve UL94-V0 rating during vertical burning tests. The nanocomposites also show significantly reduced heat release rate, demonstrating improved fire safety. Compared to traditional hybrid systems based on bisphenol A diglycidyl ether, this method avoids particle crystallization and opacity at higher filler loadings. Overall, it offers a scalable and efficient strategy for developing multifunctional high-performance materials for advanced applications.

SOLVENT-FREE PROCESSING OF HIGH β -PHASE POLY(VINYLDENE FLUORIDE) FILMS FOR ENERGY CONVERSION APPLICATIONS

L. Broggio^{1,2}, G. Moretti¹, S. Dirè¹, A. Dorigato^{1,2}

¹ Department of Industrial Engineering, University of Trento, Via Sommarive 9, 38123, Trento, Italy

² National Interuniversity Consortium of Materials Science and Technology (INSTM), Via G. Giusti 9, 50121 Florence, Italy

e-mail: lorenzo.broggio-1@unitn.it

Poly(vinylidene fluoride) (PVDF) is one of the most widely studied electroactive polymers owing to its ferroelectric properties. However, conventional processing generally promotes the non-polar α phase, limiting its electromechanical response. In this work, high β -phase PVDF films were produced through a solvent-free cold pressing and annealing process using a commercial low-cost PVDF grade. The influence of compressive stress, number of stacked layers and annealing temperature on phase transformation were investigated. The optimized process promoted the formation of the electroactive β phase and increased the piezoelectric strain coefficient (d_{33}). The proposed approach represents a simple, cost-effective and scalable route for the fabrication of electroactive PVDF films for sensing and energy-conversion applications.

HYBRID MICROGELS BASED ON PNIPAM AND NATURAL PROTEINS: FROM MOLECULAR INTERACTIONS TO BIOMATERIAL APPLICATIONS

E. Buratti¹, D. Errico¹, F. Longo^{1,2}, M. Sguizzato³, S. Buoso⁴, T. Posati⁵, G. Sotgiu^{4,5}, E. Mazzoni⁶, M. Bertoldo³

¹ Department of Environmental and Prevention Sciences, University of Ferrara, via Luigi Borsari, 46, Ferrara, 44121, Italy

² Department of Inorganic, Organic Chemistry and Biochemistry, Faculty of Chemical Sciences and Technology, University of Castilla-La Mancha, 13071 Ciudad Real, Spain

³ Department of Chemical, Pharmaceutical and Agricultural Sciences, University of Ferrara, via Luigi Borsari, 46, Ferrara, 44121, Italy

⁴ Kerline Srl, Via P. Gobetti 101, 40129 Bologna, Italy

⁵ Institute for Organic Synthesis and Photoreactivity, National Research Council (CNR-ISOF), via P. Gobetti, 101, 40129 Bologna, Italy

⁶ Department of Translational Medicine, University of Ferrara, Via Fossato di Mortara 64/B, 44121 Ferrara, Italy

e-mail: elena.buratti@unife.it

Hybrid microgels were prepared by integrating thermo-responsive PNIPAM with keratin, sericin, or fibroin extracted from textile waste, using either a synthetic pathway or physical mixing. Keratin and sericin formed stable colloidal particles via both methods, showing different covalent/physical interactions, while fibroin required physical mixing due to its high aggregation tendency. Biomedical trials revealed powerful synergistic effects between the components. Keratin integration enhanced caffeic acid encapsulation efficiency up to 90% compared to pure PNIPAM. Moreover, the hybrid thin films demonstrated outstanding dual functionality: the structural proteins successfully promoted human cell viability and growth, while the thermal transition of PNIPAM enabled smart, non-enzymatic cell detachment upon cooling.

TOWARDS SUSTAINABLE ELECTRICAL CABLE INSULATION: DESIGN OF A NOVEL POLYETHYLENE-BASED COMPOSITE SYSTEM

Maria Teresa Letizia^{1,2}, Gianluca Viscusi², Giuliana Gorrasi², Roberto Pantani²

¹University School for Advanced Studies IUSS, Pavia, Italy

²Department of Industrial Engineering, University of Salerno, Fisciano, Italy
e-mail: maria.letizia@iusspavia.it

Polyethylene (PE) is widely used for electrical insulation, but its limited mechanical strength and thermal resistance require cross-linking to improve its thermomechanical performance. Although cross-linked polyethylene (XLPE) offers excellent properties, its permanent network makes recycling difficult. Two main strategies have been proposed to improve the sustainability of PE-based insulating materials: the development of recyclable polyolefin blends or composites and the use of click chemistry-based curing. This work introduces a sustainable alternative based on an LLDPE composite containing functionalized phases reacting through thermally activated and catalyst-free reactions. The resulting material exhibited a higher Young's modulus and improved water vapor barrier properties compared with neat LLDPE.

CYCLODEXTRIN-GRAFTED CHITOSAN SCAFFOLDS FOR ENHANCED CURCUMIN DELIVERY

Elisabetta Lacolla¹, Clarissa Ciarlantini¹, Iolanda Francolini¹, Andrea Martinelli¹, Eleftheria Dossi², Marta Fernández-García³, Carolina Muñoz-Núñez³, Alexandra Muñoz-Bonilla³, Antonella Piozzi¹

¹Chemistry Department, University La Sapienza, Piazzale Aldo Moro 5, 00185 Rome, Italy

²Centre for Defence Engineering and Physical Science, Cranfield University, Defence Academy of UK, Shrivenham, SN6 8LA, UK

³Instituto de Ciencia y Tecnología de Polímeros (ICTP-CSIC), C/ Juan de la Cierva 3, 28006 Madrid, Spain

The present work focused on the development of cyclodextrin (CD)-functionalized chitosan (CS) scaffolds for curcumin (CUR) delivery. β - and γ -CDs modified with maleic or succinic anhydride were covalently grafted onto CS through EDC/NHS-mediated coupling, producing porous matrices after freeze-drying. The functionalization strategy significantly improved curcumin encapsulation efficiency compared to pristine CS, with γ CD-based systems reaching values above 80% due to the larger cavity size of γ -CD. The successful loading of CUR into the polymeric network was confirmed through FT-IR, DSC, and TGA characterization. Furthermore, the CUR-loaded systems preserved antioxidant activity and exhibited strong antibacterial properties and biocompatibility, emphasizing their potential as multifunctional biomaterials suitable for controlled drug delivery applications.

LONG VS. SHORT CHAIN COVALENT FUNCTIONALIZATION IN THE PREPARATION OF MECHANOCHROMIC POLYMERS

B. Bertoncini ^{1,2}, S. Gabellini ³, C. Adamo ¹, A. Pucci ², S. Scurti³, M. Carlotti ²

¹ Chimie ParisTech, PSL Research University, Paris, France.

² Chemistry and Industrial Chemistry Department, University of Pisa, Pisa, Italy.

³ Industrial Chemistry "Toso Montanari" Department, University of Bologna.

e-mail: stefano.scurti2@unibo.it and marco.carlotti@unipi.it

A polymeric perylene bisimide-based macromechanophore bearing poly(ϵ -caprolactone) spacers (M-PBI) was synthesized and covalently incorporated into SEBS-g-MAH and LLDPE-g-MAH matrices. Its optical, mechanical, and thermal properties were evaluated against a short-spacer analogue (P-PBI) and a physically blended system (S-PBI). Both M-PBI and P-PBI exhibited a pronounced mechanochromic response upon deformation, whereas S-PBI showed no detectable optical changes. M-PBI enabled crosslinked films while preserving the mechanical integrity of the polymer matrices. These results highlight that mechanophore architecture critically governs force transduction and mechanochromic performance in polymer systems.

EFFECT OF SILANE COUPLING AGENT CONTENT ON STRAIN-INDUCED CAVITATION IN SILICA-FILLED SBR

A. Bianucci¹, C. Marano¹

¹ Department of Chemistry, Materials and Chemical engineering "Giulio Natta", Politecnico di Milano, P.za Leonardo da Vinci 32, 20133, Milano, Italia

e-mail: alice.bianucci@polimi.it

This study investigates the effect of silane coupling agent content on strain-induced cavity formation in silica-filled styrene-butadiene rubber (SBR). The macroscopic volume variation during uniaxial tension was evaluated via Digital Image Correlation (DIC), while a microscale characterisation was performed using *in-situ* micro-CT. Both techniques showed that higher TESPT concentrations increases the material's propensity to form cavities. While increased coupling agent content was expected to strengthen the rubber-filler interface and decrease debonding, the observed behaviour is attributed to the higher crosslink density induced by the sulphur present in the coupling agent. To confirm this hypothesis, ongoing research is investigating compounds in which the sulphur content is adjusted in order to maintain constant crosslink degree.

SYNTHESIS AND NANOSTRUCTURATION OF DPP-BASED FLUORESCENT POLYESTERS FOR BIOIMAGING

Simone Gabellini, Stefano Scurti

Dept. of Industrial Chemistry "Toso Montanari", University of Bologna, Via P. Gobetti 85, 40129, Bologna, Italy

e-mail: simone.gabellini3@unibo.it

The recent advancements in fluorescent materials for bioimaging, together with the current attention on greener chemistry, led to the development of fluorescent systems made with biobased or biodegradable polymers.

In this context, diketopyrrolopyrrole (DPP) derivatives guarantee high tuneable fluorescence, high stability and the possibility to covalently incorporate it in polymeric matrix such as polyesters, obtaining a potentially biodegradable intrinsic fluorescent polymer.

This work focuses on the synthesis of emissive polymers containing DPP as the main fluorescent core, covalently integrated as a defect into a polyester derived from 1,4-butanediol and hexanedioic acid and the subsequent nanostructuring to obtain nanoparticles tested as staining dyes for bioimaging applications.

SILICA-BASED NANOSTRUCTURED MIXED OXIDES VIA SOL-GEL FOR THE ENHANCEMENT OF FIRE RESISTANCE AND RECYCLABILITY OF EPOXY RESINS

C. Imparato¹, A. Bifulco¹, G. Malucelli², S. Gaan³, A. Aronne¹

¹ Dept. of Chemical, Materials and Production Engineering, Università degli Studi di Napoli Federico II,
Piazzale Tecchio 80, 80125 Naples, Italy

² Dept. of Applied Science and Technology, Politecnico di Torino, Viale Teresa Michel 5, 15121
Alessandria, Italy

³ Empa Swiss Federal Laboratories for Materials Science and Technology, Laboratory for Advanced
Fibers, Lerchenfeldstrasse 5, 9014 St. Gallen, Switzerland
e-mail: claudio.imparato@unina.it

The development of epoxy resins requires sustainable additives for the improvement of fire resistance and innovative strategies, such as the design of covalent adaptable networks, for enabling their reprocessing. Sol-gel methodology can provide tailored mixed oxide nanofillers, either ex-situ or by in-situ growth within the epoxy matrix. Silicon-, phosphorus-, and niobium-based mixed oxides were developed as multifunctional additives using both approaches. Such fillers can promote reprocessing through transesterification of epoxy polyesters while enhancing thermal stability and fire performance, owing to their tunable acidity and porous structure. Moreover, P-modified silica nanostructures grown within the epoxy matrix achieve uniform dispersion and pave the way toward sustainable, fire-safe epoxy nanocomposites.

ELECTROSPUN MALTODEXTRIN-DERIVED CARBON FIBERS: A SUSTAINABLE PLATFORM FOR GOLD-BASED CATALYSTS

Luca Gianoglio^{1,2}, Claudio Cecone^{1,2}, Andrea Jouve³, Sara Morandi¹, Maela Manzoli⁴,
Francesco Trotta¹, Marco Zanetti^{1,2}, Pierangiola Bracco^{1,2}

¹ Department of Chemistry, University of Torino, Via Pietro Giuria, 7, 10125, Torino (TO), Italy

² SUSPLAS@UniTo, Sustainable Plastic Scientific Hub, University of Turin, Via Pietro Giuria 7,
10125 Turin, Italy

³ GAME Lab – Department of Applied Science and Technology (DISAT), Politecnico di Torino, Corso Duca
degli Abruzzi 24, 10129, Torino (TO), Italy

⁴ Department of Drug and Science and Technology, University of Torino, Via Pietro Giuria, 9, 10125,
Torino (TO), Italy

e-mail: luca.gianoglio@unito.it

The polymer industry still relies on fossil resources, motivating the development of sustainable materials. This work presents a one-step electrospinning route to carbon fibers decorated with gold nanoparticles. Maltodextrin and citric acid solutions containing $\text{HAuCl}_4 \cdot 3\text{H}_2\text{O}$ were electrospun and pyrolyzed at 700 °C under N_2 . A mild air activation treatment improved gold accessibility while preserving fiber morphology. Characterization confirmed carbon nanofibers with in-situ formed metallic Au nanoparticles. Lower Au loadings produced smaller nanoparticles and higher catalytic activity. Glycerol oxidation showed enhanced performance for small Au nanoparticles, mainly yielding glycolic acid. This study demonstrates a sustainable route for carbon-based gold catalysts for biomass valorization.

MULTIFUNCTIONAL AND SUSTAINABLE VITRIMER SYSTEMS

L. Gamberini¹, M. L. Focarete¹, L. Iannucci², C. Gotti³, M. Bartoli⁴, F. Rizzi^{5,6}, A. Zucchelli^{3,7}, M. L. Curri^{5,6,8}, S. Grassini², G. Malucelli⁹, A. Liguori¹

¹ Department of Chemistry "Giacomo Ciamician" and INSTM UdR of Bologna, University of Bologna, via P. Gobetti 85, Bologna, 40129, Italy.

² Department of Applied Science and Technology, Politecnico di Torino, Corso Duca degli Abruzzi 24, Turin, 10129, Italy.

³ Advanced Mechanics and Materials, Interdepartmental Center for Industrial Research (CIRI-MAM), University of Bologna, Viale Risorgimento 2, Bologna, 40136 Italy

⁴ Istituto Italiano di tecnologia - Center for Sustainable Future Technologies, Via Livorno 60, 10144 Torino, Italy

⁵ Institute for Chemical and Physical Processes, CNR-IPCF SS Bari, Via Orabona 4, 70126 Bari, Italy

⁶ National Interuniversity Consortium of Materials Science and Technology (INSTM), Bari Research Unit, Via Orabona 4, 70126 Bari, Italy.

⁷ Department of Industrial Engineering, University of Bologna, Viale del Risorgimento, Bologna, 40136, Italy.

⁸ Department of Chemistry, University of Bari, Via Orabona 4, 70126 Bari, Italy.

⁹ Department of Applied Science and Technology, Politecnico di Torino, Viale Teresa Michel 5, Alessandria, 15121, Italy.

e-mail: anna.liguori@unibo.it

We report a solvent-free, photocurable vitrimeric system based on bio-derived building blocks incorporating dynamic imine bonds, enabling intrinsic self-healing. The resin was UV-cured in the presence of functionalized silica nanoparticles to form crosslinked composite networks in which the nanoparticles were covalently integrated. The incorporation of 2% w/w functionalized silica nanoparticles enabled complete healing in less than five minutes at temperatures as low as 80 °C, while simultaneously imparting enhanced scratch resistance. Electrochemical impedance spectroscopy showed that pristine coatings provided excellent corrosion protection on steel substrates. The coatings were fully removed from substrates by exploiting transimination pathway of imine bonds.

FUNCTIONAL POLYMERS FOR THE OPTICAL DETECTION OF AMINES: FROM BIO-INSPIRED TO NATURAL SENSING UNITS

Angelo Nicosia¹, Lidia Mezzina¹, Laura Barone¹, Guido De Guidi¹, Placido Mineo¹

¹ Department of Chemical Sciences and INSTM UdR of Catania, University of Catania, V.le A. Doria 6,
95125, Catania, Italy
e-mail: angelo.nicosia@unict.it

Real-time monitoring of volatile amines is crucial for environmental monitoring and smart food packaging. Polymeric optical sensors offer cost-effective, instrument-free detection. Traditional bio-inspired chromophores, such as metalloporphyrins, suffer from non-green synthesis and potential toxicity. To overcome these limitations, natural pigments are ideal candidates owing to their edibility and sustainability; however, physical blending leads to unwanted dye migration. This contribution highlights the synthetic evolution toward sustainable optical sensors, focusing on the smart, covalent anchoring of natural sensing units (such as curcumin) to the polymer backbones, to prevent leaching while maintaining excellent sensing efficiency.

INTERCALATED SODIUM BENTONITE IN THERMOPLASTICIZED CORN STARCH: TUNING OXYGEN BARRIER AND MECHANICAL PERFORMANCE FOR FLEXIBLE FOOD PACKAGING APPLICATIONS

M. Righetti^{1,3}, V. Brunella^{1,2,3}, M. Zanetti^{1,2,3}

¹ Department of Chemistry, University of Turin, Via Pietro Giuria 7, 10125 Turin, Italy

² Instrm Reference Centre, University of Turin, Via G. Quarello 15A, 10135 Turin, Italy

³ SUSPLAS@UniTo, Sustainable Plastic Scientific Hub, University of Turin, Via Pietro Giuria 7, 10125 Turin, Italy

e-mail: matteo.righetti@unito.it

This study reports thermoplasticized corn starch (TPCS) bio-nanocomposite films reinforced with Sodium Bentonite (BNa, 0.5-5 wt%), prepared via solution casting, melt mixing and compression molding using glycerol as plasticizer. XRD confirmed disruption of native starch crystallinity, yielding an amorphous matrix with intercalated clay morphology that aggregated above 3 wt% filler. Oxygen permeability dropped up to 35-fold versus neat TPCS, competitive with EVOH, while Young's Modulus and tensile strength peaked at 4 wt% BNa, with reduced elongation at break. Beyond 4 wt%, aggregation slightly worsened mechanical performance, and water vapor permeability remained high due to matrix hydrophilicity, confirming TPCS/BNa as a promising oxygen-barrier packaging material.

STUDY OF THE HIGH-PRESSURE H₂ EXPOSURE EFFECT ON THE MECHANICAL BEHAVIOUR OF NBR BASED COMPOUNDS

F. Passoni¹, C. Marano¹

¹ Dipartimento Chimica, Materiali e Ingegneria Chimica "Giulio Natta", Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milano, Italy
e-mail: federico.passoni@polimi.it

Hydrogen infrastructure requires elastomeric seals capable of maintaining their mechanical integrity under high-pressure gas exposure. This work investigates three NBR-based formulations with different filler contents and matrix compositions. Specimens were exposed for 7 days to pure gaseous H₂ at 100 bar and 23 °C or at 230 bar and 70 °C. After 48 h of post-exposure storage, the mechanical behaviour was evaluated through uniaxial tensile tests and fracture tests. H₂ exposure at 100 bar and room temperature produced limited changes in mechanical properties. Conversely, the higher pressure and temperature exposure affected the mechanical behaviour, irrespectively of the gas nature. The results indicate that, for the testing conditions, pressure-temperature history plays a major role in the ageing of the studied compounds.

DEVELOPMENT AND CHARACTERIZATION OF SANDWICH COMPOSITES WITH THERMAL MANAGEMENT AND MECHANICAL PROPERTIES

L. Simonini^{1,2}, S. Santagiuliana¹, A. Tomasini¹, G. Fredi^{1,2}, A. Pegoretti^{1,2}

¹ Department of Industrial Engineering, University of Trento, Trento, Italy

² National Interuniversity Consortium of Materials Science and Technology (INSTM),
Florence, Italy

e-mail: laura.simonini@unitn.it

The increasing demand for lightweight structures with integrated thermal management capabilities has driven to the development of multifunctional composite materials. In this work, sandwiches were fabricated using an epoxy (EP) foam core embedded with microencapsulated phase change materials (PCMs) that provided thermal regulation properties to the final composites. Microstructural analyses confirmed a homogeneous distribution of PCMs within EP, while thermal tests revealed enhanced energy storage capacity with effective heat absorption and release within a targeted temperature range. Mechanical tests demonstrated that the developed sandwiches exhibited good flexural and compressive properties.

ECO-FRIENDLY DYE-PORPHYRIN COPOLYMER FOR ORGANIC SOLAR CELLS: FROM TERNARY DONOR TO INTERFACIAL LAYER

M. MARINELLI,¹ R. MEDRI,¹ E. SALATELLI,¹ M. LANZI¹

¹Dpt. Of Industrial Chemistry "Toso Montanari", University of Bologna, via Gobetti 85, 40129, Bologna, Italy.

Email: massimiliano.lanzi@unibo.it

The aim of this work is the development and step-by-step characterizations of a novel cationic thiophene based copolymer, including ionic phosphonium salt and dye-tetraphenylporphyrin (TPP) moiety in side chains, with an iconic property of solubility in a wide range of polar solvents. Synthesized by using simple, low-cost, and straightforward procedures, the material is used to fabricate completely halogen-free (i.e., from ethanol) ternary organic solar cells (OSCs). The new polymer is tested as photoactive layer and as cathode interlayer in OSCs. Furthermore, to improve and optimize the best performing device, a successful post-metallation with Zn of the porphyrin core is carried out, and a ternary OSC is fabricated, resulting in an improve in photoconversion efficiency of ~20% compared to the not-metalted one.

FURANIZED CELLULOSE NANOCRYSTALS FOR THE PREPARATION OF DIELS-ALDER RUBBER COMPOSITES

A. Riccioni^{1*}, A. Ravicini², D. Allevi², M. Fumagalli^{3,4}, R. Bongiovanni¹, V. Barbera², A. Vitale¹

¹ Department of Applied Science and Technology, Politecnico di Torino, Corso Duca degli Abruzzi 24, 10129, Torino, Italy

² Department of Chemistry, Materials and Chemical Engineering, Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milan, Italy

³ Université Claude Bernard Lyon 1, INSA Lyon, Université Jean Monnet, CNRS UMR 5223, Ingénierie des Matériaux Polymères, Boulevard du 11 novembre 1918 43, 69622, Villeurbanne, France

⁴ Univ. Grenoble Alpes, CNRS, CERMAV, Rue de la Chimie 601, 38610 Gières, France

e-mail: andrea.riccioni@polito.it

In recent years, cellulose nanocrystals (CNCs) have attracted significant interest as sustainable reinforcing agents for polymer composite materials. In this work, CNCs, extracted from hemp pulp, were functionalized with furanic groups and characterized by FT-IR and SS-NMR spectroscopy. The functionalized CNCs were used as sustainable nanofillers in rubber matrices based on furan-functionalized polybutadiene. Using a bismaleimide crosslinker, the composites were crosslinked through reversible Diels–Alder reactions. Mechanical and thermal analyses showed that the incorporation of furan-functionalized CNCs improved the elastic modulus and tensile strength compared with both the neat matrix and composites containing unmodified CNCs. Furthermore, the materials exhibited effective reprocessability, highlighting the potential of this strategy for the development of sustainable, recyclable, and high-performance rubber composites.

SMART POLYMERIC ARCHITECTURES BASED ON PHOTOSWITCHES: FROM ADHESIVES TO RESPONSIVE NANOCARRIERS

R. Rossi^{1,2}, D. Martella^{1,2}, M. Abad^{3,4}, Luis Oriol^{3,4}, M. Piñol^{3,4}, C. Parmeggiani^{1,2}

¹ Department of Chemistry, University of Florence, Via della Lastruccia 13, 50019, Sesto Firoentino, Italy

² European Laboratory for Non-Linear Spectroscopy (LENS), Via Nello Carrara 1, 50019, Sesto Firoentino, Italy

³ Instituto de Nanociencia y Materiales de Aragón (INMA), CSIC-Universidad de Zaragoza, 50009, Zaragoza, Spain

⁴ Departamento de Química Orgánica, Facultad de Ciencias, Universidad de Zaragoza, Pedro Cerbuna 12, 50009, Zaragoza, Spain

e-mail: rossir@lens.unifi.it

Arylazoisoxazoles (AIZs) show promising photoisomerization properties, enabling isothermal phase transitions or controlled polarity changes, over polymeric materials. In this work, we present the development of AIZ-based systems for two key applications: light-actuated reversible adhesives and supramolecularly functionalized micellar nanocarriers for controlled hydrophobic cargo release. Upon light irradiation, the *trans-cis* transition of AIZs allows for the modulation of adhesion strength, outperforming traditional monomers, and enables the controlled loading and release of guest molecules in Polymerization Induced Self-Assembled micelles without the need for thermal or solvent-based treatments.

ENGINEERED POLYMER-BASED COMPOSITES FOR RADIATIVE COOLING SYSTEMS

P. Stagnaro^{1a}, E. Spotorno², L. Conzatti^{1a}, S. Losio^{1b}, R. Utzeri^{1a}, F. Bisio³

¹ SCITEC-CNR, ^a Via De Marini 6, 16149 Genova, Italy; ^b Via A. Corti 12, 20133 Milano, Italy

² Dipartimento di Fisica, Università di Genova, Via Dodecaneso 33, 16146 Genova, Italy

³ SPIN-CNR, Corso Perrone 24, 16152 Genova, Italy

e-mail: paola.stagnaro@cnr.it

Urban areas are experiencing a significant rise in temperature due to the high concentration of buildings, roads, and other infrastructures that absorb and retain heat more efficiently than natural landscapes. Passive daytime radiative coolers (PDRCs) are physical systems capable of achieving a net irradiation of energy from the Earth's surface towards outer space, even under direct sunlight. To achieve this amazing feat, PDRCs require tailored photonic properties, namely high reflectivity over the solar-radiation range and selective absorbance (or equivalently emittance) in the mid-IR atmospheric transparency window (8-13 μm). Here, PDRCs made of silica-loaded polyolefin thin films hot-pressed onto Ag-coated stainless-steel slabs were fabricated and their photonic response correlated with the thermodynamic radiative efficiency.

ENHANCED HYDROLYTIC DEGRADATION OF PLA GREEN COMPOSITES BY NANOMETRIC ZNO COVALENTLY BOUND ON NATURAL FIBRES VIA ALD

L. Vitiello¹, G. Proietto Salanitri¹, A.A. Scamporrino¹, C. Laferrera², G. Impellizzeri², L. Gioiella³, G. Filippone³, S.C. Carroccio¹

¹Istituto per i Polimeri, Compositi e Biomateriali (IPCB) – CNR, Via Paolo Gaifami 18, 95126 Catania, Italia

²Istituto per la Microelettronica e Microsistemi (IMM) – CNR, Via Santa Sofia 64, 95123 Catania, Italia

³Dipartimento di Ingegneria Chimica, Dei Materiali e Della Produzione Industriale, Università di Napoli Federico II, Piazzale Tecchio 80, 80125, Napoli, Italia

e-mail: libera.vitiello@cnr.it (Inserire e-mail del corresponding author)

Biopolymers are promising alternatives to conventional plastics, although their degradation in natural environments is often limited. In this study, the degradation rate of poly(lactic acid) (PLA) was enhanced through the incorporation of ZnO nanoparticles. Green composites were developed by combining PLA with natural fibres functionalized with ZnO nanoparticles covalently anchored via atomic layer deposition (ALD). The natural fibres acted as carriers, improving nanoparticle dispersion and increasing the interfacial contact area within the polymer matrix. Hydrolytic degradation tests were carried out under different environmental conditions. The results demonstrated that fibre-bound ZnO effectively promotes PLA degradation, highlighting the potential of this strategy for the development of more environmentally responsive and sustainable biopolymer-based materials.

CAPACITIVE SENSOR BASED ON POROUS LIQUID CRYSTALLINE GEL

V. Spinoso¹, D. Martella^{1,2}, S. Nocentini^{1,3}.

¹ European Laboratory for Non-Linear Spectroscopy (LENS), University of Florence, Sesto Fiorentino, Italy
e-mail: vincenzo.spinoso@lens.unifi.it

² Department of Chemistry "Ugo Schiff", University of Florence, Sesto Fiorentino, Italy

³ National Institute of Metrology (INRiM), Torino, Italy

Capacitive temperature sensors are promising for soft and wearable electronics due to simple architecture, but their sensitivity is limited by the weak thermal response of conventional solid dielectrics. Liquid crystal materials offer higher dielectric responsiveness, yet their fluid nature limits mechanical stability and long-term operation. In this work, we present a capacitive sensor based on a Liquid Crystal Gel (LCG), where a nematic liquid crystal (5CB) is confined within a porous, crosslinked polymer matrix. The LCG functions as an active thermo-responsive dielectric combining thermally induced liquid crystal reorientation and polymer contraction. This dual mechanism, that enhances capacitive modulation, is demonstrated over repeated heating-cooling cycles in air and under water immersion.

PYROLYSIS-DERIVED TELECHELIC POLYPROPYLENE AS A MECHANOCROMIC PROBE FOR VISUALIZING STRESS REDISTRIBUTION AND CAVITATION IN POLYOLEFIN-BASED MATERIALS

B. Bertoncini^{1,2}, G. Bancalà³, C. Adamo¹, M. Carlotti², A. Pucci²

¹ Chimie ParisTech, PSL Research University, CNRS, Institute of Chemistry for Life and Health Sciences, Paris F-75005, France

² Dipartimento di Chimica e Chimica Industriale, University of Pisa, Via G. Moruzzi 13, Pisa 56124, Italy.,

³ Chemical Product Engineering, Department of Chemical Engineering, University of Groningen, Nijenborgh 3, 9747 AG Groningen, The Netherlands
e-mail: andrea.pucci@unipi.it

Controlled pyrolysis of isotactic polypropylene was used to produce pyrene-functionalized telechelic oligomers acting as mechanochromic additives. Incorporated into HDPE, LLDPE, POE, and PCL matrices, these materials enabled the visualization of deformation mechanisms through fluorescence changes. While LLDPE and PCL exhibited the expected decrease in excimer emission upon stretching, POE showed an unusual fluorescence enhancement linked to cavitation. Microscopy and scattering analyses, supported by computational investigation, revealed that void formation around polypropylene-rich domains increased the local concentration of pyrene units, promoting excimer formation. This strategy provides a simple optical method to monitor stress redistribution, interfacial debonding, and cavitation in polymer systems.

FROM HYDROPHOBIC TO HIGH-PERFORMANCE WATER FILLED POLYMERIC FILMS: A NEW PARADIGM IN WATER PURIFICATION MATERIALS

D. Riccardi¹, G. Guerra¹, P. Rizzo¹

¹ Dept. of Chemistry and Biology, INSTM Research Unit, University of Salerno, 84084 Fisciano, Italy;
e-mail: prizzo@unisa.it

This work introduces an innovative strategy for producing water-filled films of hydrophobic thermoplastic polymers without relying on hydrophilic chemical functionalization. The method is particularly effective for high-surface-area (HSA) nanoporous crystalline (NC) PPO films generated through rapid cocrystallization induced by the uptake of nonvolatile guest molecules. Water-filled HSA NC PPO films exhibit superior adsorption performance compared to sulfonated PPO and conventional polymer adsorbents, especially for removing trace organic contaminants from dilute aqueous solutions. This high efficiency highlights their potential in drinking-water purification, removal of persistent chemicals, and preconcentration of organic pollutants for analytical applications.

EMISSIVE BOTTLE-BRUSH COPOLYMERS FOR SOFT OPTO-ELECTRONIC VIA ORTHOGONAL POLYMERIZATION

S. Gabellini, R. Medri, M. Ferri, A. Luzi, E. Salatelli, M. Lanzi, D. Caretti, S. Scurti

Dept. of Industrial Chemistry "Toso Montanari", University of Bologna, Via P. Gobetti 85, 40129, Bologna, Italy

e-mail: stefano.scurti2@unibo.it

Soft optoelectronic devices require materials that combine conductivity, flexibility, and efficient light emission. Suitable diketopyrrolopyrroles-based monomer was designed to enable orthogonal polymerization reactions, generated bottle-brush architectures. This macromolecular design reduced aggregation-caused quenching by sterically separating the π -conjugated chains, leading to enhanced solid-state fluorescence while preserving electrochemical performance and stability. Furthermore, "peripheral" functionalization with specific fluorophores has led to develop FRET (Förster Resonance Energy Transfer) emitters for interactive sensing platforms. This strategy offers a versatile approach to multifunctional soft optoelectronic materials with tunable emissive and conductive properties.

EVALUATION OF THE SELF-HEALING BEHAVIOUR OF MULTIFUNCTIONAL THERMOPLASTIC COMPOSITE LAMINATES

A. Dorigato¹, L. Simonini¹, A. Sorze¹, G. Fredi¹, P. Russo², A. Pegoretti¹

¹ Department of Industrial Engineering, University of Trento, via Sommarive 9, 38123, Trento, Italy

² Institute for Polymers, Composites and Biomaterials, National Research Council, via Campi Flegrei 34,
80078, Pozzuoli, Italy
e-mail: andrea.dorigato@unitn.it

Self-healing composites are innovative materials capable of autonomously restoring mechanical properties after damage, reducing maintenance needs and extending service life. This study investigates intrinsic self-healing mechanisms in thermoplastic composites, focusing on microcrack repair activated by external stimuli (such as temperature). The research aims to develop self-healing thermoplastic matrices based on polyamide 6 (PA6) and polylactic acid (PLA), evaluating different healing agents and compatibilizers. The optimized matrices were used to manufacture fiber reinforced laminates. The results demonstrated the recovery of mechanical strength and fracture toughness, highlighting the effectiveness of the self-healing process and the potential of these composites for durable, high-performance structural applications.

FUNCTIONAL POLYMER HYBRID HYDROGELS FOR MULTI- ADSORPTION OF OPPOSITELY CHARGED EMERGENT POLLUTANTS

G. Proietto Salanitri¹, V. Giglio², D. Caretti¹, S. C. Carroccio²

¹Department of Industrial Chemistry "Toso Montanari", University of Bologna, Via Piero Gobetti 85, 40129 Bologna (Italy)

²CNR-IPCB, Via Paolo Gaifami 18, 95126, Catania (Italy)

e-mail: giuseppe.proietto3@unibo.it

The increasing occurrence of emerging pollutants in water demands multifunctional materials capable of removing diverse contaminants simultaneously. Here, functional polymer hybrid hydrogels were developed via a one-pot polymerization strategy incorporating methacrylate-functionalized mesoporous silica nanoparticles. The introduction of polymerizable methacrylate groups onto the nanoparticle surface enabled their covalent incorporation, forming a stable organic–inorganic network. This design enhances structural and mechanical properties, improves nanoparticle dispersion, and prevents leaching. The hybrid material combines complementary adsorption domains within a single platform, enabling simultaneous adsorption of emerging pollutants while enhancing structural integrity.

SHAPE-CHANGING MULTIPHASE MICROPARTICLES BASED ON LIQUID CRYSTAL EMULSIONS

C. Parmeggiani^{1,2}, M. Turriani², D. Martella^{1,2}, A. Concellón^{3,4}

¹ Dept. of Chemistry, University of Florence, via della Lastruccia 3-13, 50019, Sesto F.no, Italy

² European laboratory for Non Linear Spectroscopy (LENS), via N. Carrara 1, 50019, Sesto F.no, Italy

³ Instituto de Nanociencia y Materiales De Aragón (INMA), C/ Pedro Cerbuna, 12, 50009, Zaragoza, Spain

⁴ Dep. of Organic Chemistry, University of Zaragoza, C/ Pedro Cerbuna, 12, 5009, Zaragoza, Spain

e-mail: camilla.parmeggiani@unifi.it

Complex multiphase emulsions containing liquid crystals (LCs) offer precise morphological control and dynamic tunability, enabling applications in optics, sensing, and soft matter. Here, we report a simple and scalable bulk-emulsification strategy that circumvents the reliance on microfluidic fabrication to produce liquid crystalline network (LCN) microparticles spanning single, double (Janus), and triple emulsion morphologies within a genuinely colloidal size regime (10–20µm). Across all morphologies, the particles exhibit robust, reversible, large-amplitude deformations under heating, as well as chemoresponsivity through anisotropic swelling in organic solvents.

FABRICATION OF POROUS MICROPARTICLES BY RAFT POLYMERIZATION

Maya Rovelli, Federica Galmozzi, Michele Mauri and Roberto Simonutti
Department of Materials Science, University of Milan-Bicocca
Via R. Cozzi 55, 20125, Milano Italy
e-mail: roberto.simonutti@unimib.it

Amphiphilic PS-*b*-PDMA and P4VP-*b*-PS block copolymers with high hydrophobic fractions were synthesized via RAFT polymerization to develop stable, mesoporous nanoparticles ($p > 1$). Self-assembly was achieved through solvent exchange or via Polymerization-Induced Self-Assembly (PISA). DLS, SEM, and ^{129}Xe -NMR confirmed the formation of porous nanostructures, demonstrating high mesopore accessibility for PS-*b*-PDMA. Finally, encapsulation tests using the photosensitive molecule curcumin within the porous matrix were validated via UV-Vis spectroscopy. The complete absence of degradation products proved that these polymeric nanoparticles effectively shield and stabilize active compounds in aqueous media for advanced delivery

INVESTIGATING BACTERIA-DRIVEN ALGINATE HYDROGEL MATRIX DEGRADATION: A RHEOLOGICAL FRAMEWORK TO DISCRIMINATE BETWEEN CROSSLINKER DEPLETION AND BACKBONE CLEAVAGE

A. Fusari¹, L. Berti², S. Solhmirzaei¹, M. Petraretti², F. Villa², P. Petrini¹, F. Briatico Vangosa¹

¹ Dept. of Chimica, Materiali e Ingegneria Chimica "G. Natta", Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milano, Italy

² Dept. of Scienze per gli Alimenti, la Nutrizione e l'Ambiente, Università degli Studi di Milano, Via Luigi Mangiagalli, 25, 20133 Milano, Italy
e-mail: alice.fusari@polimi.it

Conventionally, 3D hydrogel matrices for cell encapsulation are designed as inert supports. This study challenges this paradigm by investigating the dynamic interaction between *Synechocystis* sp. PCC 6803 and calcium alginate matrices. Under nutrient starvation, a massive mechanical collapse is observed (G' dropping from kPa to Pa range). Using a rheological framework and polymer scaling theory, we decoupled two degradation mechanisms: bacterial sequestration of Ca^{2+} structural ions and enzymatic cleavage of the alginate backbone. The results demonstrate that the hydrogel acts as an active reservoir where bacteria metabolic needs drive matrix modification, transforming a simple scaffold into a responsive microenvironment.

Altri
CONTRIBUTI ORALI

Processabilità e
stampa 3D di
materiali polimerici

FROM MARINE PLASTIC LITTER TO 3D PRINTING: OPTIMISING BLENDED POLYOLEFIN FORMULATIONS FOR ADDITIVE MANUFACTURING

Bardelli A.¹, Castellano M.¹, Cavallo D.¹, M. Alloisio¹, Vicini S.¹, Demasi S.², Benvenuto L.², Mandolino C.², Frascio M.², Becherini S.³

¹ Dipartimento di Chimica e Chimica Industriale – DCCI, Università di Genova, Genova 16146, Italia

² Dipartimento di Ingegneria Meccanica, Energetica, Gestionale e dei Trasporti (DIME), Università di Genova, Genova 16146, Italia

³ Revet S.p.A., Pontedera 56025, Italia

e-mail: adrianna.bardelli@gmail.com

Le poliolefine miste (MPO) recuperate dall'ambiente marino rappresentano una risorsa in un'ottica di economia circolare. In questo studio sono state messe a punto formulazioni a base MPO additivate con antiossidante, compatibilizzante e biofiller, le quali sono state caratterizzate mediante analisi termiche, reologiche, morfologiche e meccaniche. I risultati hanno evidenziato un incremento della stabilità termossidativa, una migliore processabilità e un comportamento reologico idoneo alla stampa 3D alimentata a granuli. Inoltre, l'azione sinergica di compatibilizzante e biofiller ha favorito l'adesione interfacciale e migliorato le proprietà meccaniche rispetto all'MPO non additivato. Lo studio conferma il potenziale delle plastiche marine come materiali funzionali per la manifattura additiva.

In Situ Stereocomplex Formation During Melt Extrusion: An Efficient Nucleating Strategy for Crystallization of High-Molecular-Weight PLA

Rocco Di Girolamo¹, Massimo Christian D'Alterio,¹ Lorenzo Lombardi,² Alessandra Cicoella,¹ Antonio Ascione,¹ Sonia Stornaiuolo,¹ Pier Luca Maffettone,² Claudio De Rosa¹

¹Department of Chemical Sciences, University of Naples Federico II, Naples, Italy

²Department of Chemical, Materials and Production Engineering, University of Naples Federico II, Italy

e-mail: rocco.digirolamo@unina.it

In this study we demonstrate that melt extrusion induces the crystallization of poly(lactic acid) (PLA) stereocomplexes (SC) in blends of high-molecular-weight PDLA/PLLA containing up to 12% stereodefects. The amount and thermal stability of the SC phase depend on blend composition and processing conditions. Despite their low concentration, in situ formed SC crystallites act as highly efficient nucleating agents for the α -form of PLA, with nucleation efficiencies ranging from ~60% to nearly 100%. The strongest nucleating effect was observed in blends containing moderately stereodeficient PLLA. These results provide a simple, fully bio-based approach to tailor the crystallization kinetics and crystalline morphology of industrially relevant high-molecular-weight PLA without the need for conventional nucleating agents.

EFFECT OF NATURAL FILLERS AS SUBSTITUTES FOR GLASS FIBERS IN POLYAMIDE 6 COMPOSITES FOR LARGE-FORMAT ADDITIVE MANUFACTURING

A. Sorze¹, F. Valentini¹, N. Soligo², L. Pasquardini^{3,4}, A. Dorigato¹

¹ Department of Industrial Engineering, University of Trento, Via Sommarive 9, 38123, Trento, Italy

² Tessilquattro S.p.A., Via Linfano 9, 38062 Arco, Italy

³ Indivenire Srl, Via Sommarive 18, 38123 Trento, Italy

⁴ Department of Engineering, University of Campania Luigi Vanvitelli, Via Roma 29, 81031 Aversa, Italy

e-mail: alessandro.sorze@unitn.it

This work investigated clay, silica, and calcium carbonate as sustainable alternatives to glass fibers (GF) in PA6 composites for Large-Format Additive Manufacturing (LFAM) applications. Natural filler-reinforced formulations (≤ 10 wt%) were produced and compared with a 30 wt% GF reference. Rheological and thermal analyses showed that the fillers preserved the thermal behavior of PA6 while providing suitable processability for LFAM. Printing trials demonstrated good print quality and filler dispersion. Flexural testing revealed a good mechanical response and reduced anisotropy compared to the GF-reinforced composite. Despite their significantly lower loading, the selected natural fillers provided competitive performance, highlighting their potential as lightweight and sustainable reinforcements for LFAM applications.

INFLUENCE OF GRAPHENE ON THE ELECTRICAL AND MECHANICAL PROPERTIES OF SLS-PRINTED PA11

E. Togliatti^{1,2}, C. Sciancalepore^{2,3}, F. Toniato³, R. Giovanardi^{1,4}, H. Andersson⁵, L. Bond⁵, Magnus Larsson⁶, Magnus Engholm⁵, D. Milanese^{2,3}

¹ Dipartimento di Ingegneria e Architettura, Università degli Studi di Parma, Parco Area delle Scienze 181/a, 43124, Parma, Italy

e-mail: elena.togliatti@unipr.it

² INSTM, Consorzio Interuniversitario per la Scienza e Tecnologia dei Materiali, Firenze, Italy

³ Dipartimento di Ingegneria dei Sistemi e delle Tecnologie Industriali, Università degli Studi di Parma, Parco Area delle Scienze 181/a, 43124, Parma, Italy

⁴ Dipartimento di Ingegneria Enzo Ferrari, Università di Modena e Reggio E., Modena, Italy

⁵ Department of Engineering, Mathematics and Science Education, Mid Sweden University, Sundsvall, Sweden

⁶ 2D fab AB, Montörvägen 7, SE-853 50, Sundsvall, Sweden

This study focused on the production of innovative bio-based polyamide 11 (PA11) composites reinforced with 2 wt.% graphene (PA11G) via Selective Laser Sintering (SLS), with the aim of developing multifunctional materials suitable for advanced applications in food and healthcare, such as 3D-printed sensors and smart devices. PA11 reinforced with 1wt.% biochar was used as a reference (PA11B). After printing dumbbell specimens, PA11G shows improved consolidation and a more compact structure by microscopic analysis, and a reduced crystallinity through DSC, confirmed by FT-IR amide group analysis. The findings also demonstrated that, in comparison to reference samples, graphene enhances the composite's stiffness, and electrical conductivity due to the formation of conductive network.

FUSED FILAMENT FABRICATION OF TPU/PCM COMPOSITES FOR THERMALLY ACTIVE WEARABLE SPORT APPLICATIONS

D. Rigotti^{1,2}, A. Dorigato^{1,2}, A. Pegoretti^{1,2}

¹ Department of Industrial Engineering, University of Trento, via Sommarive 9, 38123, Trento, Italy

² National Interuniversity Consortium of Materials Science and Technology (INSTM),
Florence, Italy

e-mail: danielle.rigotti-1@unitn.it

Flexible TPU composites containing microencapsulated phase-change materials were developed for fused filament fabrication of thermally active wearable components. The printed materials retained significant latent heat storage capability with good stability after thermal cycling. Increasing PCM content improved thermal functionality but reduced ductility and fatigue resistance, especially because of porosity in printed samples. Under compressive fatigue, mechanical stiffness decreased markedly, while melting and crystallization enthalpies remained largely preserved, generally above 80%. These results show that thermal functionality is more robust than mechanical performance, making TPU/PCM composites promising for customized thermally active insoles and sport wearables.

EXTENDING RUBBER FRACTURE CHARACTERIZATION METHODS TO LAYER ADHESION ASSESSMENT IN 3D-PRINTED TPU

Andrea Caccini¹, Shiva Khoshtinat¹, Manuel Sardinha², Maria de Fatima Reis Vaz²,
Sofia Teixeira Freitas², Claudia Marano¹

¹ Department of Chemistry, Materials and Chemical Engineering “Giulio Natta”
Politecnico di Milano, Milan MI 20133, Italy

.....
² 2IDMEC, Instituto Superior Técnico, Universidade de Lisboa, Av Rovisco Pais, 1049-001 Lisbon,
Portugal
e-mail: andrea.caccini@polimi.it

This study investigates the feasibility of extending experimental methods for the characterisation of fracture behaviour in bulk rubber to evaluate layer adhesion in 3D-printed TPU specimens. The effects of printing temperature, layer thickness, and external cooling were systematically evaluated by measuring the J-integral, an energy-based fracture parameter, both at fracture onset and during the crack growth. A layer thickness of 0.2 mm provides the highest J-integral values, while increasing the printing temperature to 240°C only slightly improves fracture performance, with external cooling having a negligible effect.

Altri
CONTRIBUTI ORALI

Chimica e fisica dei
polimeri

ELECTROSPUN MEMBRANES OBTAINED FROM PLANT PROTEINS AND MALTODEXTRINS FOR THE TREATMENT OF GADOLINIUM- CONTAMINATED WASTEWATER

C. Cecone¹ – F. Alchera¹ – L. Gianoglio¹ – A. Scarciglia² – E. Di Gregorio² – G.
Ferrauto² – M. Ginepro¹ – P. Bracco¹

¹ Department of Chemistry, University of Turin, Via Pietro Giuria 7, 10125, Turin, Italy

² Department of Molecular Biotechnologies and Health Sciences, University of Turin, Via Nizza 52, 10126, Turin, Italy

e-mail: claudio.cecone@unito.it

The use of gadolinium-based contrast agents in MRI has led to the contamination of water resources. To address this issue, this study focuses on developing innovative biodegradable filtration membranes. These membranes were produced through electrospinning using zein and maltodextrins. Maltodextrin membranes have proven to be highly effective in removing free gadolinium, while activated carbon was incorporated into both zein and maltodextrin fibers to help retain complexed gadolinium. Tests showed successful removal in both aqueous solutions and simulated urine. However, efficiency significantly decreased when tested in real environmental matrices. Further optimization is needed to improve performance and viability for large-scale applications.

FROM AMPHIPHILIC RANDOM COPOLYMERS TO FUNCTIONAL NANO-CHELATORS: A NEW STRATEGY FOR RADIONUCLIDES SEQUESTRATION

M. Turriani^{1,2}, M. Giomi¹, L. Menichetti³, D. Petroni³, F. Casavecchia³, M. Lessi^{1,2,4},
E. Rosadoni¹, E. Guazzelli^{1,2,4}, E. Martinelli^{1,2,4}

¹Department of Chemistry and Industrial Chemistry, University of Pisa, Via G. Moruzzi 13, 56124, Pisa, Italy

²National Interuniversity Consortium of Materials Science and Technology (INSTM), Via G. Giusti 9, Florence, Italy (UdR Pisa)

³Institute of clinical physiology (IFC), CNR, Via G. Moruzzi 1, 56124, Pisa, Italy

⁴Center for Instrument Sharing of the University of Pisa (CISUP), University of Pisa, Lungarno Pacinotti 43/44, 56126, Pisa, Italy

e-mail: marco.turriani@ospiti.unipi.it

PEGMA-based amphiphilic random copolymers enable the formation of nano-objects below 20 nm through intramolecular single-chain folding, yielding unimolecular, or unimer, micelles. Their LCST-like thermoresponsiveness allows stimulus-controlled aggregation, potentially exploitable for material recovery. In this work, amphiphilic random copolymers bearing oxyethylene and short fluorinated side chains as well as covalently linked DOTA-type chelating units were synthesized by RAFT polymerization. Their self-assembly and thermoresponsive behavior in water were studied by DLS and turbidimetry, while ⁶⁸Ga and ^{99m}Tc sequestration was assessed by radio-TLC. A proof of concept for chelating copolymer recovery is also presented.

A NOVEL MELAMINE-FREE WATERBORNE INTUMESCENT COATING FOR FIRE PROTECTION OF WOOD

Lorenzo Tosato¹, Daniele Caretti¹, Stefano Scurti¹, Elena Minelli²

¹Dept. of Industrial Chemistry "Toso Montanari", Università di Bologna, Bologna, Italy

²JF Amonn S.r.l., Ponte nelle Alpi, Belluno, Italy

e-mail: lorenzo.tosato2@unibo.it

Wood is a renewable and sustainable construction material, but its high flammability limits its use in building applications. A melamine-free waterborne intumescent coating based on a urea–formaldehyde (UF) binder was developed, optimized, and successfully scaled up. The formulation showed good storage stability, reproducibility, and free formaldehyde content below 0.1 wt.%. Rheological analysis revealed shear-thinning behavior, confirming suitability for industrial application. Fire performance assessed by cone calorimetry, showed excellent fire protection properties. In parallel, ammonium polyphosphate modified additive (APP–EA–PCL) is being investigated as a multifunctional flame retardant combining carbon, nitrogen, and phosphorus sources within a single component, potentially replacing the conventional intumescent triad.

ELECTROSPINNING AND SOLUTION BLOW SPINNING OF WATER-BASED POLYMER SOLUTIONS FOR THE SUSTAINABLE MANUFACTURING OF NANOFIBROUS MATS

J.A. Talamo Ruiz¹, V. Veitengruber², M. Retsch², L. Pattelli³, A. Vitale¹

¹ Department of Applied Science and Technology, Politecnico di Torino, 10129, Torino, Italy

² Department of Chemistry, Physical Chemistry I, University of Bayreuth, 95447, Bayreuth, Germany

³ Istituto Nazionale di Ricerca Metrologica, 10135, Torino, Italy

e-mail: jessica.talamo@polito.it

ABSTRACT

The sustainable production of nanofibrous materials requires fabrication techniques that combine morphological control, scalability, and environmentally benign processing. This work compares electrospinning (ES) and solution blow spinning (SBS) for producing nanofibrous mats from a fully aqueous poly(vinyl pyrrolidone) (PVP) solution, directly assessing the influence of the spinning mechanism on fiber morphology. Both techniques successfully produced continuous nanofibers: ES yielded highly uniform fibers (~980 nm) with a narrow diameter distribution, whereas SBS generated thinner fibers (~430 nm) with greater size variability. These results demonstrate the feasibility of producing water-based nanofibrous mats while enabling control of fiber morphology for applications requiring tailored porosity and light scattering.

TACTICITY-INDEPENDENT CRYSTALLIZATION AS A DESIGN STRATEGY FOR CHEMICALLY RECYCLABLE SEMICRYSTALLINE POLYMERS

Miriam Scoti, Claudio De Rosa

Dipartimento di Scienze Chimiche, Università di Napoli Federico II, via Cintia 80126, Napoli, Italy

e-mail: miriam.scoti@unina.it (corresponding author)

Crystallization improves thermal and mechanical properties of synthetic polymers, but it usually requires high stereo- and regioregularity of the polymer molecular structure. Recent polyesters and polythioesters chemically recyclable to their monomers have revealed the phenomenon of tacticity-independent crystallization, as they are able to crystallize despite their stereoirregular or even atactic microstructure. Here, the crystal structures of stereoregular and atactic mono- and dimethylated poly(3-hydroxybutyrate)s and of poly(2-thiabicyclo[2.2.1]heptan-3-one) are discussed to identify the molecular factors responsible for tacticity-independent crystallization. These case studies provide design rules for semicrystalline, chemically recyclable polymers without the need for enantiopure monomers or highly stereoselective catalysts.

STRUCTURE-PROPERTY RELATIONSHIPS IN BIOPOLYMERIC CRYOGELS PRODUCED BY FREEZE-CASTING

G. Pignatiello¹, G. Filippone¹, V. Ambrogi¹, M. Salzano de Luna¹

¹ Department of Chemical, Materials and Production Engineering, University of Naples Federico II, P.le
Tecchio 80, 80125, Napoli, Italy
e-mail: giacchino.pignatiello@unina.it

Cryogels are a very versatile and advantageous material, thanks to their low density, high specific surface and low thermal conductivity. This work aims to investigate this type of materials obtained by freeze-casting starting from a biopolymer solution, selecting a series of different production conditions that allow obtaining samples differing in microstructure and, consequently, with different properties and so different advantages in the applications. To evaluate the effect of the different process parameters, the samples obtained are characterized by density and porosity measurements, observation under a scanning electron microscope, compression tests and, after cross-linking, water absorption kinetics.

PRESSURE-INDUCED CRYSTALLIZATION AND POLYMORPHIC TRANSITIONS OF POLYBUTENE-1: HIGH-PRESSURE PVT STUDY

F.Olla¹, F. Briatico Vangosa¹

¹Department of Chemistry, Materials, and Chemical Engineering "Giulio Natta", Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133 Milano, Italy

Isotactic poly(1-butene) exhibits complex pressure-sensitive polymorphism, yet quantitative volumetric data remains limited. High-pressure PVT dilatometry was employed to monitor specific-volume changes during melt crystallization between 10 and 200 MPa. Results reveal that crystallization yields predominantly form II at $P \leq 60$ MPa, while hydrostatic pressure accelerates the solid-solid $II \rightarrow I$ transformation at 75–100 MPa. Beyond ≥ 175 MPa, form I' dominates. From these dilatometric fingerprints, phase-resolved $V(T,P)$ maps were successfully assembled. These findings offer practical inputs for shrinkage prediction and delineate pressure protocols to suppress metastable form II, mitigating delayed dimensional changes.

HEMIN-BASED AMPHIPHILIC RANDOM COPOLYMERS AS BIOMIMETIC AND RECYCLABLE CATALYSTS FOR ARGET-ATRP IN WATER

E. Guazzelli^{1,2}, M. Turriani^{1,3}, C. Sissa⁴, A. Delledonne⁴, M. Fantin⁵, A. Antonello⁵ E. Martinelli^{1,2}

¹ Department of Chemistry and Industrial Chemistry, University of Pisa, Pisa, Italy

² Center for Instrument Sharing of the University of Pisa (CISUP), University of Pisa, Pisa, Italy

³ National Interuniversity Consortium of Materials Science and Technology (INSTM), Florence, Italy (UdR Pisa)

⁴ Department of Chemical, Life and Environmental Sustainability Sciences, University of Parma, 43124 Parma, Italy

⁵ Department of Chemical Sciences, University of Padova, Via Marzolo 1, 35131 Padova, Italy

e-mail: elisa.guazzelli@unipi.it

Hemin represents a promising bioderived iron catalyst; however, its poor water solubility and challenging recovery still limit its practical application. Here, thermoresponsive amphiphilic random copolymers bearing short PEG and fluorinated side chains were designed as polymeric nanoplateforms to stabilize hemin in water, while enabling its recovery above their typical cloud point temperature. The copolymers were synthesized by RAFT polymerization and investigated in terms of aqueous self-assembly, LCST-type behavior, hemin incorporation, and electrochemical activity of the metal center. Their potential as biomimetic catalysts for aqueous ARGET-ATRP was assessed polymerizing PEGMA₅₀₀. The results support the development of bio-inspired and recyclable catalysts for sustainable aqueous controlled radical polymerization.

i
POSTERS

i
POSTERS

Polimeri da fonti
rinnovabili e
degradabili, riciclo

DEVELOPMENT OF CELLULOSE FIBERS RECOVERY STRATEGY FROM SILICONIZED PAPERS

B. Cavallo¹, V. Brunella¹, C. Barolo¹

¹ Dept. of Chemistry, Università di Torino, Via P. Giuria 7, 10125, Torino, Italia

e-mail: beatrice.cavallo@unito.it

Release liners are the paper substrates left after pressure-sensitive labels are peeled off and applied. They consist of highly refined cellulose fibers with a smooth surface, coated with a thin layer of polydimethylsiloxane (PDMS) that imparts release properties, but hinders the recyclability of the liners. This work proposes a strategy to remove silicone and recover cellulose fibers, by disintegration under controlled alkaline and thermal condition, to swell the fibers, followed by a surfactant-assisted flotation step that removes the silicone particles formed during pulping. The cleaned pulp is then formed into handsheet samples and characterized by FTIR, XRF, SEM-EDS and mechanical testing. This process enables the reuse of the desiliconized pulp as a valuable secondary raw material for the papermaking process.

PBAT/GRAPE POMACE BIOCOMPOSITE FOR FILM BLOWING APPLICATIONS

M. Ceraulo^{1,2}, M.C. Mistretta^{1,2}, L. Botta^{1,2}, Indovino E.^{1,2}, V. Gelarda¹, M. Leanza³, M. Rapisarda³, P. Rizzarelli³

¹ Department of Engineering, University of Palermo, Palermo, Italy

²National Interuniversity Consortium of Materials Science and Technology (INSTM),
Florence, Italy

³ Institute of Polymers, Composites and Biomaterials - National Research Council (IPCB-CNR), Catania,
Italy

The study explores the use of grape pomace (GP), a wine industry by-product, as a biofiller in biodegradable polymer films to promote sustainability and circular economy. GP is rich in lignocellulosic and antioxidant compounds, making it suitable for polymer enhancement. A masterbatch with PBAT was produced via twin-screw extrusion and used to create films containing 5% and 10% GP. The materials were tested for processability, rheological behavior, mechanical properties, aging, and biodegradability. Results showed good filmability with adequate melt strength and stretching behavior. Mechanical performance remained acceptable, with no significant embrittlement. GP influenced photo-oxidation and biodegradation kinetics. Overall, GP demonstrates strong potential for developing sustainable packaging films through film blowing.

ANTIOXIDANT AND UV-BLOCKING POLY(BUTYLENE SUCCINATE) FILMS VIA NITROXIDE RADICAL COUPLING FUNCTIONALIZATION

S. Coiai^{1*}, N. Migliore¹, E. Passaglia¹, R. Spiniello¹, C. Gambarotti², F. Cicogna¹

¹ Istituto di Chimica dei Composti OrganoMetallici (ICCOM), Consiglio Nazionale delle Ricerche, via G. Moruzzi 1, 56124 Pisa, Italia

² Dipartimento di Chimica, Materiali e Ingegneria Chimica "Giulio Natta", Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133 Milano, Italia
e-mail: serena.coiai@cnr.it

Poly(butylene succinate) (PBS) was functionalized via nitroxide radical coupling (NRC) using a TEMPO derivative bearing a sterically hindered phenolic antioxidant group (BHB-TEMPO). The reaction was conducted in both solution and melt phases, yielding covalently bound antioxidant functionalities while preserving the molecular and thermal properties of PBS. The melt-phase process achieved the highest degree of functionalization. The resulting functionalized films demonstrated improved resistance to thermo-oxidative and photo-oxidative degradation, as well as effective UV-blocking properties. Notably, the most highly functionalized sample protected β -carotene from UV-induced degradation, indicating its potential for use in biodegradable, compostable active food packaging.

THERMAL METHOD TO RECOVER GLASS FIBERS FROM EPOXY RESIN COMPOSITES

E. Di Francesco¹, N. Parodi¹, R. Freccero¹, A. Pastorino¹, D. Cavallo¹, M. Alloisio¹, M. Castellano¹, S. Vicini¹

¹ Dipartimento di Chimica e Chimica Industriale (Università di Genova, DCCI, Via Dodecaneso 31, 16165 Genova, Italia).

.....
e-mail: eleonora.di.francesco@edu.unige.it

The accumulation of end-of-life wind turbine blades has a significant environmental impact due to the limited recycling options for glass fiber reinforced polymers. Mechanical recycling damages glass fibers and produces low-value fillers, while chemical methods are expensive and difficult to scale up. This work proposes induction heating as an alternative thermal recycling process to preserve the integrity of glass fibers. Fiber degradation is reduced compared to conventional pyrolysis by minimizing the direct contact of the fibers with the high-temperature environment. The recovered fibers present an uniform organic residue that has been evaluated as a compatibilizer in the production of new composites. The process appears scalable, uses recyclable conductor materials, and has the potential to reduce overall recycling costs.

INFLUENCE OF FAST PYROLYSIS BIO-OIL-DERIVED PHENOLIC-RICH FRACTION FROM LOGGING RESIDUES ON PLLA UV STABILITY

D. Duraccio¹, M. Di Maro¹, G. Gomez d'Ayala², G. Dal Poggetto², Taina Ohra-aho³, Elmeri Pienihäkkinen³, Petri Widsten³, Giulio Malucelli⁴

¹ Istituto di Scienze e Tecnologie per L'Energia e La Mobilità Sostenibili CNR Sede Secondaria Strada Delle Cacce, 73 10135 Torino, Italy

² Istituto per i Polimeri, Compositi e Biomateriali (IPCB) Via Campi Flegrei 34, Comprensorio "A. Olivetti" 80078 Pozzuoli (Na), Italy

³ VTT Technical Research Centre of Finland Ltd., Tekniikantie 21, 02150 Espoo, Finland

⁴ Politecnico di Torino - Dipartimento di Scienza Applicata e Tecnologia, Viale Teresa Michel 5, 15121 Alessandria, Italy

e-mail: mattia.dimaro@stems.cnr.it

The development of new biodegradable polymer formulations is essential to address the depletion of fossil resources and the environmental issues associated with conventional plastics. A novel PLLA-based blend containing 2 wt.% phenolic-rich fraction of fast pyrolysis bio-oil (FPBO), obtained from logging residues, was prepared and investigated to evaluate its behavior under UV ageing. Changes in structure, morphology, and mechanical properties during UV exposure were analyzed. Samples were subjected to UV irradiation for up to 23 days, and their ageing behavior was evaluated after 7 and 23 days in comparison with non-aged counterparts. The blend exhibited remarkable resistance to UV irradiation, retaining its functional properties even after 23 days of exposure, whereas the embrittlement of unfilled PLLA was already evident after 7 days.

Polyethylene Glycol-Assisted Film Stacking of Polylactide/Bacterial Cellulose Nanocomposites for Sustainable Food Packaging

Zonta E.^{1,2,3}, Mantovani S.^{1,2}, Fredi G.^{1,2}

¹ Department of Industrial Engineering, University of Trento, Via Sommarive 9, 38123 Trento, Italy.

² National Interuniversity Consortium of Materials Science and Technology (INSTM), Florence, Italy.

³ Bioniks srl, Via della Segheria 1/H, 37141 Montorio (VR), Italy.

e-mail: giulia.fredi@unitn.it

ABSTRACT

Bacterial cellulose (BC) is a renewable nanofibrillar material with high purity, biocompatibility and excellent specific mechanical properties, making it a promising reinforcement for biodegradable polymers. This work investigates PLA/BC nanocomposites prepared by film stacking and hot pressing, using PEG pre-impregnation of BC to improve processability and interfacial adhesion. PEG plasticization increased BC strain at break up to six-fold and promoted PLA penetration into the network, yielding well-bonded laminates. The optimized composites showed improved mechanical performance, reduced O₂/CO₂ permeability, UV-barrier behaviour, retained transparency, low water uptake and industrial compostability, highlighting their potential for sustainable food packaging.

Biopol4Soil - BIODERIVED POLYMERIC GRANULES AND NON-WOVEN FABRICS FOR SUSTAINABLE AGRICULTURE: BIODEGRADABILITY AND PHYTOTOXICITY EVALUATION

L. Gianoglio^{1,3} – A. Boarino^{2,3} – C. Cecone^{1,3} – S. Celletti^{2,3} – M. Zanetti^{1,3} – E. Padoan^{2,3}

¹ Department of Chemistry, University of Turin, Via Pietro Giuria 7, 10125, Turin, Italy

² Department of Agricultural, Forest and Food Sciences (DISAFA), University of Turin, Largo Paolo Braccini 2, Grugliasco, 10095, Turin, Italy

³ SUSPLAS@UniT, Sustainable Plastic Scientific Hub, University of Turin, Via Pietro Giuria 7, 10125 Turin, Italy

e-mail: luca.gianoglio@unito.it

The Biopol4soil project investigates bioderived cross-linked maltodextrin granules and electrospun maltodextrin/zein non-woven fabrics for agricultural applications. Neutral and cationic maltodextrin granules exhibited remarkable water retention capacities between 622% and 734%, demonstrating potential for deployment in soil remediation and soil conditioning. Biodegradation studies in simulated soil solutions confirmed the progressive weight loss and microbial accessibility over an eight-week testing period. Soil incubation tests revealed that non-woven fabrics underwent full biodegradation within two weeks in sub-alkaline soil characterized by high microbial biomass. In contrast, biodegradation in microbial biomass acid soil proceeded more slowly, with the hydrophobic zein protein content noticeably retarding structural breakdown.

CHARACTERIZATION OF HYDROLYZED POLYESTERS FROM AGRO-WASTE: EFFECT OF EXTRACTION CONDITIONS ON COMPOSITION

C. Meo¹, E. Buratti², M. Calosi¹, I. Dedieu³, A. Montanari³, T. Barbieri³, M. Bertoldo¹

¹ Dept. of Chemical, Pharmaceutical and Agricultural Sciences,
University of Ferrara, Via L. Borsari 46, 44121, Ferrara, Italy

² Dept. of Environmental and Prevention Sciences, University of Ferrara, Via L. Borsari 46, 44121, Ferrara, Italy

³ Tomapaint Srl, via Roma 4, S. Ilario D'Enza, 42049, Reggio Emilia, Italy
e-mail: cristina.meo@unife.it

The requirement to develop sustainable coatings has shifted the focus toward biobased polymers obtained from the valorization of agro-industrial byproducts. In this study, the effect of the main alkaline hydrolysis parameters on the composition of cutin extracted from tomato peels was investigated. The samples were characterized using NMR, IR-ATR, acid-base titration, GPC, and DSC. The analyses revealed that hydrolysis efficiency increased as the treatment temperature rose. GPC analysis showed significant variations in the percentages of oligomers, dimers, and monomers. DSC analysis confirmed the presence of a crystalline phase in all samples. The results provide useful information for optimizing cutin extraction processes for the development of sustainable coatings.

INFLUENCE OF GLOCHIDS AND COMPATIBILIZER ON THE RHEOLOGICAL, MECHANICAL AND BIODEGRADATION BEHAVIOUR OF PBAT AND PLA BIOCOMPOSITES

M.C. Mistretta¹, L. Botta¹, E. Indovino¹, G. Lalia¹, P. Rizzarelli², M. Rapisarda², M. Leanza², M. Bianchi³, A. Dorigato³

¹ Dept. of Engineering, Università di Palermo, Viale delle Scienze, 90128, Palermo, Italia

² Institute of Polymers, Composites and Biomaterials - National Research Council (IPCB-CNR), Via Paolo Gaifami 18, Catania, Italia

³ Department of Industrial Engineering (DII), Via Sommarive 9, 38123, Trento, Italia
e-mail: mariachiara.mistretta@unipa.it

This study investigates the use of glochids as a bio-filler in biodegradable polymer matrices, focusing on PBAT and PLA to clarify how the filler interacts with different polymer systems. Because fillers and matrices often show limited compatibility, a compatibilizer was also incorporated to enhance interfacial adhesion. The findings indicate that glochids and the compatibilizer play distinct roles in PBAT and PLA-based biocomposites. Glochids increase stiffness and viscosity in both matrices. The compatibilizer further raises viscosity at low shear rates and intensifies non-Newtonian behaviour, although the magnitude of these effects depends on the specific matrix. This suggests that the compatibilizer functions as a chain extender differently in PBAT and PLA. Its presence also alters the biodegradation kinetics of the resulting materials.

CIRCULAR VALORIZATION OF POST-CONSUMER POLYURETHANE FOAMS THROUGH MECHANICAL RECYCLING AND SUSTAINABLE COMPOSITE DESIGN

J. Martignetti ¹, L. D'Arienzo ¹, L. Incarnato ^{1,2}, P. Scarfato ^{2,3}

¹ Dept. of Industrial Engineering, University of Salerno, Via Giovanni Paolo II, 132 – 84084 Fisciano (SA), Italy

² INSTM, National Interuniversity Consortium of Materials Science and Technology, Via G. Giusti, 9 – 50121 Florence, Italy

³ Dept. of Civil Engineering, University of Salerno, Via Giovanni Paolo II, 132 – 84084 Fisciano (SA), Italy
e-mail: pscarfato@unisa.it

The sustainable management of end-of-life polyurethane (PU) foams is a major challenge due to their thermoset nature. In this work, flexible PU foams from discarded mattresses were mechanically recycled through cryogenic grinding and compression molding to obtain densified panels. The effects of foam composition and processing parameters on material performance were investigated. Furthermore, volcanic ash was incorporated as a sustainable mineral filler to develop composite materials with enhanced properties. The recycled panels exhibited good structural integrity, improved thermal stability, and satisfactory mechanical performance, demonstrating the potential of this approach for producing value-added products.

ITACONIC ACID: A SUSTAINABLE PLATFORM ALTERNATIVE TO ACRYLIC ACID IN RADICAL POLYMERIZATION

Tsvetevelina Georgieva, Michele Mauri and Roberto Simonutti

Department of Materials Science, University of Milan-Bicocca
Via R. Cozzi 55, 20125 Milano, Italy
e-mail: roberto.simonutti@unimib.it

Acrylate polymers are industry standards for coatings and adhesives but lack sustainability and biodegradability. Itaconic acid derivatives offer bio-based alternatives, though limited by slow radical polymerization kinetics. This study employs RAFT polymerization to overcome these constraints, optimizing conditions using various chain transfer agents (CTAs) and initiators. Dithiobenzoates provided excellent molecular weight control for dimethyl itaconate (DMI), while the low-temperature initiator Vazo 70 significantly accelerated reaction rates compared to AIBN for dibutyl itaconate (DBI). The resulting DBI polymers exhibited film-forming characteristics with glass transition temperatures between -5 °C and 15 °C. Furthermore, poly(DMI) acted as an efficient macro-CTA to synthesize well-defined amphiphilic block copolymers containing itaconic acid. Ultimately, self-assembly of these amphiphilic systems successfully yielded monodisperse polymeric nanoparticles measuring 20–30 nm.

BIOBASED VITRIMERS USING EUTECTIC HARDENER SYSTEMS

S. Zeynalova¹, R. Bongiovanni¹, A. Vitale¹, S. Dalle Vacche¹

¹ Politecnico di Torino, Department of Applied Science and Technologies

Corso Duca degli Abruzzi 24, 10129 Turin, Italy

e-mail: sakina.zeynalova@polito.it

This work details the synthesis of fully bio-derived vitrimers cured via a green, non-toxic deep eutectic hardener. Dynamic covalent networks were fabricated by combining a cashew nutshell-derived epoxy resin with lignin-based diglycidyl ether of vanillyl alcohol (DGEVA), employing a 1:1 malic acid/ethyl lactate eutectic mixture as the crosslinker alongside zinc triflate as transesterification catalyst. The curing kinetics of mixtures with different blending ratios were analysed by DSC and FT-IR spectroscopy, and the thermal, mechanical, and dynamic properties of the resulting vitrimers were evaluated. The proposed approach provides a sustainable route toward high bio-based-content vitrimers obtained from renewable feedstocks and environmentally benign curing systems.

i
POSTERS

Materiali polimerici
ibridi e
(nano)compositi
sintesi,
caratterizzazione e
applicazioni

GRAPHENE OXIDE FUNCTIONALIZATION OF BACTERIAL CELLULOSE: EFFECTS ON THE STRUCTURE AND ADSORPTION PERFORMANCE

Erika Caianiello¹, Federico Olivieri¹, Martina Aulitto², Rachele Castaldo¹, Roberto Avolio¹, Maria Emanuela Errico¹, Patrizia Contursi², Gennaro Gentile¹, Mariacristina Cocca¹

1. Institute for Polymers, Composites and Biomaterials National Research Council of Italy, via Campi Flegrei 34, 80078, Pozzuoli (NA), Italy

2. University of Naples Federico II, Biology Department, via Cinthia 26, 80126, Napoli, Italy

e-mail: erikacaianiello@cnr.it

This study investigates bacterial cellulose (BC) composites as sustainable adsorbent materials for removing organic contaminants from water. BC was produced as biofilms and beads, with graphene oxide (GO) added during bacterial growth to improve its adsorption properties. The resulting materials were chemically, morphologically, and thermally characterized and evaluated for the removal of Rhodamine 6G, Methyl Orange, and 2,4-dichlorophenol. Adding GO improved structural uniformity, thermal stability, and adsorption efficiency, allowing for the capture of anionic and neutral contaminants that regular BC could not remove effectively. Additionally, the interconnected porous network of the composites shows their potential for capturing micro- and nanoplastics from water.

RESIDUAL ANTIOXIDANT ACTIVITY OF WINERY BY-PRODUCT BIOFILLERS IN LDPE AND HDPE COMPOSITES

F.Cicogna^{1*}, E. Passaglia¹, A. Nanni², M. Buono^{2,3}, M. Colonna³, A. Fortunelli¹, S. Coiai¹

¹ Istituto di Chimica dei Composti OrganoMetallici (ICCOM), Consiglio Nazionale delle Ricerche, via G. Moruzzi 1, 56124 Pisa, Italia

² AgroMateriae srl, Via Granarolo 177/3, 48018 Faenza (RA), Italia

³ Dipartimento di ingegneria civile, chimica, ambientale e dei materiali, Università di Bologna, Via U. Terracini 28, 40131, Bologna, Italy
e-mail: francesca.cicogna@cnr.it

Two winery by-product biofillers derived from grape seeds (WGS B1 and WGS GV3) were compared with commercial tannins and synthetic antioxidants (Irganox 1010 and B225). Thermal stability was assessed by TGA, and functional groups by ATR-FTIR. DPPH results, benchmarked against Trolox, showed that biofillers retain significant antioxidant activity. Biofillers and reference additives were melt-compounded with LDPE and HDPE at 180°C, maintaining a constant tannin content (0.8 wt.%). Composites were characterized by DSC and TGA, showing improved thermal stability. The antioxidant effect was further confirmed by thermal aging at 110°C. Notably, biofillers effectively transferred their antioxidant activity to the polymer matrices. These findings highlight the potential of untreated biofillers as multifunctional stabilizing additives.

UPCYCLING HAZELNUT BY-PRODUCTS INTO FUNCTIONAL ELASTOMERIC COMPOSITES FOR SUSTAINABLE SPORTS SURFACES

L. Conzatti^{1a}, R. Utzeri^{1a}, L. Visentin^{1b}, F. Zaccheria^{1b}, M. Guidotti^{1b}, I. Nedi², G. Lesage²

¹ Institute of Chemical Sciences and Technologies "Giulio Natta" (SCITEC), CNR: ^a Via De Marini 6, 16149 Genova, Italy; ^b Via C. Golgi 19, 20133, Milano, Italy

² MONDO S.p.A., P.le E. Stroppiana 1, 12051, Alba (Cn), Italy
e-mail: lucia.conzatti@cnr.it

Elastomeric compounds for sports flooring applications were developed using hazelnut-derived and bio-based additives and compared with a reference formulation containing conventional additives. Epoxidized hazelnut oil was used as plasticizer, lignin as antioxidant, and gallic acid immobilized on inorganic supports (silica, saponite, kaolin) to replace filler and antioxidant simultaneously. Tensile testing showed that most formulations exhibited mechanical properties comparable to the reference, with increased stiffness for the silica-based system and minor variations for the others. Lignin-based compounds showed slightly higher strength, whereas the saponite-based system was slightly weaker. These results confirm the feasibility of replacing conventional rubber additives with bio-based alternatives within a circular economy framework.

DEVELOPMENT OF LIGNIN-CONTAINING BIODEGRADABLE POLYMER BLENDS FOR FISHING NET APPLICATIONS

Roberta D'AURIA^{1*}, Roberto AVOLIO¹, Rachele CASTALDO¹, Maria Emanuela
ERRICO¹, Gennaro GENTILE¹, Immacolata LIOTTA¹, Federico Olivieri¹, Mariacristina
COCCA¹.

¹Institute for Polymers, Composites and Biomaterials National Research Council of Italy, via Campi
Flegrei, 34 80078 Pozzuoli (NA), Italy
e-mail: robertadauria@cnr.it

Plastic pollution caused by abandoned fishing nets is a major threat to marine ecosystems due to ghost fishing. Biodegradable PBS/PBAT blends were developed as sustainable materials for fishing net applications. Lignin was incorporated as a natural UV absorber to enhance photostability and promote controlled degradation under sunlight. Different formulations were prepared by varying the lignin content and characterized through chemical, physical, and rheological analyses. Polymeric films were exposed to both natural and artificial UV radiation to evaluate their degradation behavior. Changes induced by UV exposure were investigated using colorimetric, morphological, and thermal analyses. The results confirmed the effectiveness of lignin in tailoring the UV response while maintaining suitable processability. These findings support the development of biodegradable fishing nets with reduced environmental impact.

PREPARATION AND CHARACTERIZATION OF THERMORESPONSIVE FILMS OBTAINED FROM HYBRID PNIPAM/SILK FIBROIN SYSTEMS

D. Errico¹, T. Posati², M. Bertoldo³, E. Buratti¹.

¹ Dept. of Environmental and Prevention Sciences, University of Ferrara, Via L. Borsari 46, 44121, Ferrara, Italy.

² Consiglio Nazionale delle Ricerche, Istituto per la Sintesi Organica e la Fotoreattività (CNR-ISOF), via Piero Gobetti 101, Bologna 40129, Italy

³ Dept. of Chemical, Pharmaceutical and Agricultural Sciences,
University of Ferrara, Via L. Borsari 46, 44121, Ferrara, Italy.
e-mail: **davide.errico@unife.it**

Poly(N-isopropylacrylamide) (PNIPAM) is a thermoresponsive polymer used for biomedical applications. In this work, PNIPAM/fibroin (SF) blends were prepared by physical mixing of preformed 650 nm and 300 nm PNIPAM microgels with SF solution. The resulting stable colloidal dispersion were used for obtaining homogeneous thin films. FT-IR spectroscopy confirmed both the presence of PNIPAM and SF within the hybrid materials. Thermal treatment (60–160 °C) significantly improved film stability in aqueous media. Swelling degrees at 25 and 40 °C showed thermoresponsiveness consistent with hydrophilic-to-hydrophobic transition of PNIPAM across its critical temperature. These findings highlight the potential of PNIPAM/SF hybrid films as sustainable and stimuli-responsive biomaterials.

DEVELOPMENT OF PBSA-BASED BIOCOMPOSITES REINFORCED WITH *CEIBA SPECIOSA* NATURAL FIBRES

V. Fiore¹, L. Botta¹, G. Iacono¹, C. Sciancalepore², N. Badalamenti³, M. Bruno³

¹ Dept. of Engineering, Università di Palermo, Viale delle Scienze, 90128, Palermo, Italia

² Dept. of Engineering for Industrial Systems and Technologies, Università di Parma, Parco Area delle Scienze 181/A, 43124, Parma, Italia

³ Dept. of Biological, Chemical and Pharmaceutical Sciences and Technologies, Università di Palermo, Viale delle Scienze, 90128, Palermo, Italia
e-mail: vincenzo.fiore@unipa.it

This work reports the development of biodegradable biocomposite laminates based on a poly(butylene succinate-co-adipate) (PBSA) matrix reinforced with the cottony seed floss of *Ceiba speciosa* (silk floss tree) fruit. Laminates were manufactured by the film-stacking technique, using the fibre both in flock form, as a core layer between PBSA skins, and in microparticle form, melt-blended into the skins themselves. In the first campaign, neat PBSA skins were combined with a core of untreated or NaHCO₃-treated flock fibres at two weight concentrations. In the second campaign, untreated flock fibres were combined with skins filled with 5 wt% of untreated or NaHCO₃-treated particles. The resulting sandwich laminates, which combined macro- and micro-scale reinforcement, achieved the highest stiffness among all tested configurations.

STABILIZATION OF MAGNETIC NANOPARTICLES IN LIQUID CRYSTALLINE POLYMERS VIA TAILOR-MADE LIGANDS

T. Landovský¹, G. Barrera², F. Celegato², P. Tiberto², D. Martella^{3,4}, C. Parmeggiani^{3,4}

¹ Institute of Physics of the Czech Academy of Sciences, 182 00 Prague 8, Czechia

² Department of Advanced Materials Metrology and Life Science, Istituto Nazionale di Ricerca Metrologica (INRiM), 10135 Torino, Italy

³ Department of Chemistry "Ugo Schiff", University of Florence, 50019 Sesto Fiorentino, Italy

⁴ European Laboratory for Non-Linear Spectroscopy (LENS), 50019 Sesto Fiorentino, Italy
e-mail: landovsky@fzu.cz

Efficient mixing of magnetic nanoparticles (MNPs) with liquid crystalline (LC) matrices remains a key challenge in the preparation of corresponding composites. In this context, coating MNP surface with organic ligands that ensure their compatibility with the LC environment is one of the most promising approaches. In this contribution, we present the use of tailor-made ligands for the stabilization of MNPs in mixtures with compounds typically used for the preparation of LC polymers. Superparamagnetic magnetite NPs were first coated with specifically designed ligands and subsequently introduced in the nematic LC solvent 5CB and in its mixture with LC cross-linker RM257. The second material enabled us to prepare self-standing films after polymerization. Finally, the magnetic properties of all obtained materials were investigated.

PHYSICS-INFORMED MACHINE LEARNING FOR PREDICTING OPTICAL TRANSMITTANCE AND HAZE IN TRANSPARENT WOOD

D. Nuvoli¹, A. Bifulco², D. Pugliese³, A. Casciello², M. Terzi⁴, A. Mariani¹, G. Malucelli⁶

¹ Department of Chemical, Physical, Mathematical, and Natural Sciences, University of Sassari, Via Vienna 2, Sassari 07100, Italy

² Department of Chemical, Materials and Production Engineering, University of Naples Federico II, 80125 Naples, Italy

³ Division of Applied Metrology and Engineering, National Institute of Metrological Research (INRiM), Torino 10135, Italy

⁴ Division of Quantum Metrology and Nanotechnologies, National Institute of Metrological Research (INRiM), Torino 10135, Italy

⁵ Dept. of Applied Science and Technology, Politecnico di Torino, Viale T. Michel 5, 15121, Alessandria, Italy
e-mail: giulio.malucelli@polito.it

Transparent wood (TW) is an emerging sustainable material whose optical performance depends on a complex interplay between composition, thickness, refractive index matching, and microstructure. Here, a physics-informed machine learning framework was developed to predict optical transmittance and haze using a literature-derived dataset of 95 transparent wood systems. Random Forest, Gradient Boosted Trees, and Multilayer Perceptron models were evaluated after robust preprocessing, missing-data imputation, and controlled data augmentation. Optical transmittance was predicted with good accuracy, whereas haze remained more challenging due to its strong dependence on microstructural heterogeneity. The results demonstrate the potential of machine learning as a tool for accelerating TW design and optimization.

PREPARATION AND CHARACTERIZATION OF UV-LED CURABLE BIO-BASED COATINGS CONTAINING POLYMERIC CARBON DOTS

M. Bartoli¹, E. Piatti², G. Malucelli³

¹ Istituto Italiano di tecnologia - Center for Sustainable Future Technologies, Via Livorno 60, 10144 Torino, Italy

² Dept. of Applied Science and Technology, Politecnico di Torino, C.so Duca degli Abruzzi 24, 10129, Torino, Italy

³ Dept. of Applied Science and Technology, Politecnico di Torino, Viale T. Michel 5, 15121, Alessandria, Italy
e-mail: giulio.malucelli@polito.it

Bio-based UV-curable coatings represent a promising route toward sustainable advanced materials. In this work, polymeric carbon dots (PCDs) synthesized from citric acid and 1,4-phenylenediamine through an ultrasound-assisted process were incorporated into an acrylated epoxidized soybean oil (ESBOA) resin and UV-LED cured. The resulting coatings retained the characteristic fluorescence emission of the nanofiller while achieving complete photopolymerization. Thermal analyses revealed that PCDs slightly improved the thermal stability of the coatings without affecting the glass transition temperature or crosslinking density. These findings demonstrate the potential of polymeric carbon dots as multifunctional bio-derived nanofillers for fluorescent UV-LED curable coatings.

SUSTAINABLE TRANSPARENT WOOD BASED ON BIO-BASED ISOBORNYL ACRYLATE/METHACRYLATE MATRICES

A. Cabras¹, D. Nuvoli¹, D. Pugliese², M. Terzi³, A. Mariani¹, G. Malucelli⁴

¹ Dept. of Chemical, Physical, Mathematical, and Natural Sciences, University of Sassari, Via Vienna 2, Sassari 07100, Italy

² Division of Applied Metrology and Engineering, National Institute of Metrological Research (INRiM), Torino 10135, Italy

³ Division of Quantum Metrology and Nanotechnologies, National Institute of Metrological Research (INRiM), Torino 10135, Italy

⁴ Dept. of Applied Science and Technology, Politecnico di Torino, Viale T. Michel 5, 15121, Alessandria, Italy
e-mail: giulio.malucelli@polito.it

Transparent wood (TW) is an emerging sustainable material combining the hierarchical structure of wood with the optical properties of transparent polymers. In this work, delignified balsa wood was filled with bio-based poly(isobornyl acrylate) (polyBOA), poly(isobornyl methacrylate) (polyBOMA), and their copolymers. The developed composites exhibited high optical transmittance (up to 80%), significant light diffusion, low thermal conductivity ($0.15\text{--}0.18\text{ W m}^{-1}\text{ K}^{-1}$), and homogeneous polymer distribution within the wood structure. The results demonstrate that isobornyl-based polymers are promising sustainable alternatives to conventional petroleum-derived matrices for transparent wood applications in energy-efficient buildings, optical devices, and advanced functional materials.

MICROPLASTICS RELEASE FROM PP-BASED BLENDS AND NANOCOMPOSITES

M. Morreale¹, E. Indovino², M. Baiamonte², V. Titone², L. Botta^{2,3}, F.P. La Mantia^{2,3}

¹ Dept. of Engineering and Architecture, Università di Enna "Kore", Cittadella Universitaria, 94100, Enna, Italy

² Dept. of Engineering, Università di Palermo, Viale delle Scienze, 90128, Palermo, Italy

³ National Interuniversity Consortium for Science and Technology of Materials (INSTM), Via Giusti 9, 50121, Firenze, Italy

e-mail: marco.morreale@unikore.it

Microplastics and nanoplastics release into the environment is a very important issue with significant threats in terms of environmental and health impact. A typical case is when they are generated from the degradation and fragmentation processes affecting plastic-based items mainly due to environmental and mechanical factors. It is further interesting to focus on multiphase polymer systems, such as polymer blends and nanocomposites, since microplastics (and, possibly, nanoplastics) could be generated both from the dispersed phase and the matrix. In this work, we focused on two polypropylene/polyester blends without and with a suitable compatibilizer, and a polypropylene nanocomposite with a commercial nanoclay, and their microplastics release due to photo-oxidation and mechanical stress was investigated.

i
POSTERS

Processabilità e
stampa 3D di
materiali polimerici

PROCESSING AS A DESIGN TOOL FOR TAILORING MICROSTRUCTURE AND PROPERTIES IN COMPLEX POLYMER SYSTEMS

R. Arrigo¹, A. Frache¹

¹ Dept. of Applied Science and Technology, Politecnico di Torino, Viale Teresa Michel 5, 15121, Alessandria, Italia

e-mail: rossella.arrigo@polito.it

Complex polymer-based systems often require more than compositional design: their final behavior is strongly governed by the microstructure generated during processing. This contribution highlights processing as an active design tool through three case studies in which the selection and optimization of the processing route are used to control morphology and material properties. Specifically, elongational flow compatibilizes PLA/PHBH blends, improving ductility; mixing sequence in HDPE/PA6/nanoclay blends controls clay localization and fire behavior; FFF of PP/nanoclay generates FR structures more effective than traditional technologies. Overall, these examples demonstrate that processing/microstructure/properties relationships can be deliberately exploited to design polymer systems with tailored performances.

i

POSTERS

Chimica e fisica dei
polimeri

FLUORINE-FREE PROTON EXCHANGE MEMBRANES: SYNTHESIS AND CHARACTERIZATION OF SULFONATED PPO-PBI NETWORKS FOR PEMWES

BANDINI¹, CARLOTTI¹, GIOVANELLI¹, GUAZZELLI¹, PUCCI¹

¹Dipartimento di Chimica e Chimica Industriale, University of Pisa, Via G. Moruzzi 13, 56124 Pisa, Italy

e-mail: a.bandini8@studenti.unipi.it

(INSERIRE UN ABSTRACT DI NON PIU' DI 8 RIGHE)

Green hydrogen production via PEM water electrolyzers (PEMWE) is limited by the cost and environmental impact of perfluorinated membranes like Nafion. This study presents novel, fluorine-free proton exchange membranes based on sulfonated polyphenylene oxide (PPO-SO₃H) crosslinked with polybenzimidazole (PBI). PBI crosslinking provided robust structural integrity, restricting swelling below Nafion 117 levels while maintaining excellent thermo-mechanical stability. Crucially, optimized PPO-SO₃H-PBI membranes achieved an outstanding ion exchange capacity (IEC) of 1.44 mmol/g, outperforming the Nafion 117 benchmark (0.93 mmol/g) via synergistic proton conduction. These architectures demonstrate exceptional potential as cost-effective, high-performance solid polymer electrolytes for next-generation PEMWEs

TOWARDS CIRCULAR FLAME-RETARDED POLYPROPYLENE: FIRE PERFORMANCE AFTER RECYCLING AND AGING

A. Frache¹, R. Arrigo¹

¹ Dept. of Applied Science and Technology, Politecnico di Torino, Viale Teresa Michel 5, 15121, Alessandria, Italia

e-mail: alberto.frache@polito.it

Plastics circularity requires flame-retarded (FR) materials retaining fire safety after service-life and recycling. Here, FR polypropylene (PP) circularity was investigated through two approaches. First, intumescent FRs or magnesium hydroxide were introduced into reprocessed PP to assess whether recycled matrices can be upgraded for fire-safe applications. Second, FR-PPs were subjected to repeated reprocessing cycles to evaluate fire-performance retention after mechanical recycling. FR properties remained nearly unchanged compared with virgin FR-PP, or even improved due to more efficient char formation, while mechanical properties and processability were preserved. Finally, thermo- and photo-oxidative aging before reprocessing was addressed, enabling a more realistic assessment of FR-PP circularity.

DESIGN OF CARBAZOLE-FUNCTIONALIZED POLY(TRIPHENYLAMINE)S FOR VISIBLE-DRIVEN WATER REMEDiation

Muhammad Furqan Farooq¹, Martina Recupero¹, Olga Sacco¹, Vincenzo Venditto¹,
Vincenzo Vaiano² and Stefania Praqliola¹

¹ Department of Chemistry and Biology "A. Zambelli" and INSTM Research Unit, University of Salerno, via
Giovanni Paolo II, 132, 84084 Fisciano (Salerno), Italy

² Department of Industrial Engineering, University of Salerno, via Giovanni Paolo II, 132, 84084 Fisciano
(Salerno), Italy
e-mail: spragliola@unisa.it

Carbazole-functionalized polytriphenylamines (PTPAs) were synthesized via oxidative polymerization using iron(III) chloride. Two para-substituted monomers bearing 9H-carbazole and 3,6-dimethyl-9H-carbazole units yielded amorphous polymers (PM1 and PM2) with moderate molecular weights (≈ 5 kDa) and good film-forming ability. PM2 exhibits higher chloroform solubility due to suppressed cross-linking induced by methyl substitution. PM1 shows an optical band gap of 2.90 eV, consistent with visible-light responsiveness. Preliminary photocatalytic tests using methylene blue demonstrated efficient dye removal under visible light, indicating that these PTPAs are promising photoactive materials for environmental applications.

XXVI Convegno Nazionale



ASSOCIAZIONE ITALIANA di SCIENZA
e TECNOLOGIA delle
MACROMOLECOLE



Torino, 6-9 Settembre 2026

Organized by



UNIVERSITÀ
DI TORINO



Politecnico
di Torino



UNIVERSITÀ DEL PIEMONTE ORIENTALE

Supported by



Anton Paar

METTLER TOLEDO

